

Project Name:	Type:
Part Number:	Date:



GREENCREATIVE

Value Select A Lamp Family

FEATURES

- Suitable to replace 40W, 60W, 75W, 100W Incandescent
- Comfortable diffused light
- Smooth dimming with existing dimmers*
- Suitable for use in damp locations
- Operating temperature: -4°F / -20°C to +95°F / +35°C
- Rated Lifetime (L70): 25,000hrs
- 3 year limited warranty



SPECIFICATIONS


Product	Model	Equiv.	Wattage (W)	CCT	Lumens	Efficacy (LPW)	Input Voltage	Beam Angle	CRI	Dim.*	Power Factor	Base	Fixture Rating	Lifetime (L70) (hrs)	Cert.
97985	6A19DIM/827/R	40W	6	2700K	480	80	120V	220°	82	Yes	0.9	E26	Non-Enclosed	25,000	ES
97986	6A19DIM/830/R	40W	6	3000K	480	80	120V	220°	82	Yes	0.9	E26	Non-Enclosed	25,000	ES
98011	8A19DIM/827/R	60W	8	2700K	800	100	120V	220°	82	Yes	0.9	E26	Non-Enclosed	25,000	ES
98012	8A19DIM/830/R	60W	8	3000K	800	100	120V	220°	82	Yes	0.9	E26	Non-Enclosed	25,000	ES
98013	8A19DIM/840/R	60W	8	4000K	800	100	120V	220°	82	Yes	0.9	E26	Non-Enclosed	25,000	ES
97908	9A19DIM/827/GU24/R	60W	9	2700K	800	89	120V	240°	82	Yes	0.9	GU24	Enclosed	25,000	ES
97909	9A19DIM/830/GU24/R	60W	9	3000K	820	91	120V	240°	82	Yes	0.9	GU24	Enclosed	25,000	ES
97910	9A19DIM/840/GU24/R	60W	9	4000K	860	96	120V	240°	82	Yes	0.9	GU24	Enclosed	25,000	ES
98138	11A19DIM/827	75W	11	2700K	1100	100	120V	240°	82	Yes	0.9	E26	Enclosed	25,000	ES
98139	11A19DIM/830	75W	11	3000K	1150	105	120V	240°	82	Yes	0.9	E26	Enclosed	25,000	ES
98140	11A19DIM/840	75W	11	4000K	1200	109	120V	240°	82	Yes	0.9	E26	Enclosed	25,000	ES
98144	15A21DIM/827	100W	15	2700K	1600	107	120V	240°	82	Yes	0.9	E26	Enclosed	25,000	ES
98145	15A21DIM/830	100W	15	3000K	1650	110	120V	240°	82	Yes	0.9	E26	Enclosed	25,000	ES
98146	15A21DIM/840	100W	15	4000K	1700	113	120V	240°	82	Yes	0.9	E26	Enclosed	25,000	ES
98150	15A21DIM/827/GU24	100W	15	2700K	1600	107	120V	240°	82	Yes	0.9	GU24	Enclosed	25,000	ES
98083	14A19/827/3WAY	40W 60W 100W	4 8 14	2700K	500 1000 1500	125 125 107	120V	230°	82	No	0.9	E26d	Non-Enclosed	15,000	ES

* This lamp might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.




Value Select A Lamp Family


DIMENSIONS & WEIGHT





Model	Base	MOL	Dia.	Weight
6A19DIM/xxx/R	E26	4-3/16"	2-3/8"	0.07lb
8A19DIM/xxx/R	E26	4-3/16"	2-3/8"	0.08lb




Model	Base	MOL	Dia.	Weight
9A19DIM/xxx/GU24/R	GU24	4-3/16"	2-3/8"	0.11lb



Model	Base	MOL	Dia.	Weight
11A19DIM/xxx	E26	4-7/16"	2-3/8"	0.13lb



Model	Base	MOL	Dia.	Weight
15A21DIM/xxx	E26	5-7/16"	3"	0.23lb
15A21/xxx/GU24	GU24	5-1/2"	3"	0.26lb



Model	Base	MOL	Dia.	Weight
14A19/xxx/3WAY	E26d	4-5/8"	2-3/8"	0.25lb



Value Select A Lamp Family

MINIMUM COMPARTMENT DIMENSIONS		
Model	Diameter	Height
6A19DIM/xxx/R	6"	8-1/2"
8A19DIM/xxx/R	6"	8-1/2"
9A19DIM/xxx/GU24/R	6"	8-1/2"
11A19DIM/xxx	6"	8-1/2"
15A21DIM/xxx	6"	8-1/2"
15A21/xxx/GU24	6"	8-1/2"
14A19/xxx/3WAY	6"	8-1/2"

Installing lamp in a fixture that does not have the minimum compartment dimensions will void the warranty and could cause product failures.