

Project Name:	Type:
Part Number:	Date:



GREENCREATIVE

DIRECT T5

FEATURES

- Plug & Play – Easy to install
- Compatible with a wide range of ballasts including 0-10v dimmable models*
- Exceptional high efficacy up to 152 LPW
- Opaque plastic lens reduces glare
- 270° extra wide light emitting area
- Suitable for enclosed luminaires and damp locations
- Plastic and aluminum design meets NSF requirements and eliminates breakage
- Fixture operating temperature: -4°F to 95°F (-20°C to 35°C)
- Lamp ambient temperature: -4°F to 113°F (-20°C to 45°C)
- Rated lifetime (L70): 60,000hrs
- 5 year limited warranty** / 10 year available (see EXTENDED WARRANTIES table for information)
- Suitable for all indoor general lighting application
- NSF (National Sanitation Foundation) certified for Food Zone (Non-Contact), Splash, and Non-Food Zones



DIGITAL NAVIGATION

Explore the spec sheet through the links below

BALLAST PERFORMANCE	DIMENSION & WEIGHT
LOGISTIC INFORMATION	EXTENDED WARRANTIES
CERTIFICATION INFORMATION	



SPECIFICATIONS

Product	Model	Nominal Length	Equiv.	Input Voltage	Wattage (W)	Lumens	CCT	Efficacy (LPW)	CRI	Power Factor	THD	Beam Angle	Dim.*	Fixture Rating	DLC	DOE
57958	8T5HE/2F/830/DIR	2'	14W	120-277V	8	950	3000K	119	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
57959	8T5HE/2F/835/DIR	2'	14W	120-277V	8	950	3500K	119	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
57960	8T5HE/2F/840/DIR	2'	14W	120-277V	8	1,100	4000K	138	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
35669	8T5HE/2F/850/DIR	2'	14W	120-277V	8	1,100	5000K	138	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
57954	12T5HE/3F/830/DIR	3'	21W	120-277V	12	1,420	3000K	118	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
57955	12T5HE/3F/835/DIR	3'	21W	120-277V	12	1,420	3500K	118	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
57956	12T5HE/3F/840/DIR	3'	21W	120-277V	12	1,550	4000K	125	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
97929	15T5HE/4F/830/DIR/R	4'	28W	120-277V	15	2,200	3000K	147	82	0.9	<20%	120°	Yes	Enclosed	✓	✓
97930	15T5HE/4F/835/DIR/R	4'	28W	120-277V	15	2,200	3500K	147	82	0.9	<20%	120°	Yes	Enclosed	✓	✓
97931	15T5HE/4F/840/DIR/R	4'	28W	120-277V	15	2,250	4000K	150	82	0.9	<20%	120°	Yes	Enclosed	✓	✓
98165	10.5T5HO/2F/830/DIR	2'	24W	120-277V	10.5	1,500	3000K	143	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
98166	10.5T5HO/2F/835/DIR	2'	24W	120-277V	10.5	1,500	3500K	143	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
98167	10.5T5HO/2F/840/DIR	2'	24W	120-277V	10.5	1,600	4000K	152	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
35667	10.5T5HO/2F/850/DIR	2'	24W	120-277V	10.5	1,600	5000K	152	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
98168	14.5T5HO/3F/830/DIR	3'	39W	120-277V	14.5	2,050	3000K	142	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
98169	14.5T5HO/3F/835/DIR	3'	39W	120-277V	14.5	2,050	3500K	142	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
98170	14.5T5HO/3F/840/DIR	3'	39W	120-277V	14.5	2,200	4000K	152	82	0.9	<20%	120°	Yes	Enclosed	N.A.	✓
97924	24T5HO/4F/830/DIR/R	4'	54W	120-277V	24	3,450	3000K	144	82	0.9	<20%	120°	Yes	Enclosed	✓	N.A.
97925	24T5HO/4F/835/DIR/R	4'	54W	120-277V	24	3,450	3500K	144	82	0.9	<20%	120°	Yes	Enclosed	✓	N.A.
97926	24T5HO/4F/840/DIR/R	4'	54W	120-277V	24	3,500	4000K	146	82	0.9	<20%	120°	Yes	Enclosed	✓	N.A.
97927	24T5HO/4F/850/DIR/R	4'	54W	120-277V	24	3,500	5000K	146	82	0.9	<20%	120°	Yes	Enclosed	✓	N.A.

FOOTNOTES:
 * Please refer to www.greencreative.com for complete ballast / dimmer compatibility list
 ** Please visit www.greencreative.com for Limited Warranty terms.

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.




DIRECT T5

BALLAST PERFORMANCE

Model	Bare Lamp Wattage (W)	System Wattage (W)	3000K Lumens	3500K Lumens	4000K Lumens	5000K Lumens
8T5HE/2F/xxx/DIR	8	10	950	950	1,100	1,100
12T5HE/3F/xxx/DIR	12	15	1,420	1,420	1,550	-
15T5HE/4F/xxx/DIR/R	15	18	2,200	2,200	2,250	-
10.5T5HO/2F/xxx/DIR	10.5	14	1,500	1,500	1,600	1,600
14.5T5HO/3F/xxx/DIR	14.5	18	2,050	2,050	2,200	-
24T5HO/4F/xxx/DIR/R	24	29	3,450	3,450	3,500	3,500

Testing Method: Above system power is half the total system power of a 2-tube installation using an Instant Start ballast. Power and lumen output will vary based on ballast and fixture type.
Above data is indicative only

DIMENSION & WEIGHT



Model	Base	MOL	Dia.	Weight
8T5HE/2F/xxx/DIR	G5	22-1/16"	11/16"	0.17lb
12T5HE/3F/xxx/DIR	G5	33-31/32"	11/16"	0.27lb
15T5HE/4F/xxx/DIR/R	G5	45-3/4"	11/16"	0.42lb
10.5T5HO/2F/xxx/DIR	G5	22-1/8"	11/16"	0.18lb
14.5T5HO/3F/xxx/DIR	G5	33-15/16"	11/16"	0.26lb
24T5HO/4F/xxx/DIR/R	G5	45-3/4"	11/16"	0.42lb

Where xxx means 824-965 which indicates CRI and color temperature

LOGISTIC INFORMATION

Model	Master Carton			Shipping Carton		
	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight
8T5HE/2F/8xx/DIR	6PCS	22-15/16" x 2-1/2" x 1-3/4"	1.51lb	24PCS	25-3/16" x 5-13/16" x 4-13/16"	6.53 lb
12T5HE/3F/8xx/DIR	6PCS	34-13/16" x 2-1/2" x 1-3/4"	2.26 lb	24PCS	37-1/8" x 5-13/16" x 4-13/16"	9.74 lb
15T5HE/4F/8xx/DIR/R	6PCS	46-5/8" x 2-1/2" x 1-3/4"	2.99 lb	24PCS	47-1/16" x 5-13/16" x 4-13/16"	12.86 lb
10.5T5HO/2F/8xx/DIR	6PCS	22-15/16" x 2-1/2" x 1-3/4"	1.48 lb	24PCS	25-3/16" x 5-13/16" x 4-13/16"	6.43 lb
14.5T5HO/3F/8xx/DIR	6PCS	34-13/16" x 2-1/2" x 1-3/4"	2.24 lb	24PCS	37-1/8" x 5-13/16" x 4-13/16"	9.65 lb
24T5HO/4F/8xx/DIR/R	6PCS	46-5/8" x 2-1/2" x 1-3/4"	2.99 lb	24PCS	47-1/16" x 5-13/16" x 4-13/16"	12.86 lb

EXTENDED WARRANTIES***

Model	Description****
8T5HE/2F/DIR/10YEARWARRANTY	10 Year warranty for 8T5HE/2F/8xx/DIR/yy
12T5HE/3F/DIR/10YEARWARRANTY	10 Year warranty for 12T5HE/3F/8xx/DIR/yy
15T5HE/4F/DIR/10YEARWARRANTY	10 Year warranty for 15T5HE/4F/8xx/DIR/yy
10.5T5HO/2F/DIR/10YEARWARRANTY	10 Year warranty for 10.5T5HO/2F/8xx/DIR/yy
14.5T5HO/3F/DIR/10YEARWARRANTY	10 Year warranty for 14.5T5HO/3F/8xx/DIR/yy
24T5HO/4F/DIR/10YEARWARRANTY	10 Year warranty for 24T5HO/4F/8xx/DIR/yy

FOOTNOTES:

*** Warranty based on a maximum of 4,368 annual operating hours (per year for ten years) and exposure to a maximum fixture operating temperature of 80°F / 27°C.

**** xx – Refers to the CCT yy – Refers to model generations within the same nominal performance. Typically blank, 'R', or 'RC'

CERTIFICATION INFORMATION

Product	Model	DLC ID#
97929	15T5HE/4F/830/DIR/R	PB48J6K3
97930	15T5HE/4F/835/DIR/R	P925XSEC
97931	15T5HE/4F/840/DIR/R	PZXBQ4S
97924	24T5HO/4F/830/DIR/R	P1QBZSCH
97925	24T5HO/4F/835/DIR/R	PTMQBB5E
97926	24T5HO/4F/840/DIR/R	PVDSTDK2
97927	24T5HO/4F/850/DIR/R	P54SW12S

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.