



T5 15W HE 4FT. DIR GL

MODEL

Model: 15T5HE/4F/xxx/GL/DIR

Where xxx means 824-965 which indicated
CRI and color temperature



EMERGENCY BALLAST COMPATIBILITY

Brand	Model	Compatibility
Bodine	B30ST	OK
Bodine	B50	OK
Bodine	B54	OK
Bodine	B60	OK
Bodine	B100	X
Bodine	LP550	OK
Bodine	LP600	OK
Iota	I-42-EM-R-J	OK
Iota	I-320	OK
Iota	ICE-80	X
Iota	I-232	OK
Iota	I-32	OK
Iota	ISL-54	OK
Iota	ISL-540	OK
Iota	ISD-80	OK
Lithonia	EI500	OK
Lithonia	PSQ500QD	X
Lithonia	PS1400QD	OK
Fulham	FH4-DUAL-700L	X
Fulham	FH3-DUAL-450	X
Fulham	FH5-DUAL-1400L	OK
ALP	EFP 32GS	X

OK = Fully Compatible

X = Incompatible

*GREEN CREATIVE has provided this emergency ballast compatibility chart for guidance when selecting an emergency ballast and lamp combination. Lamps were tested for compatibility with the above listed emergency ballasts. Emergency ballasts that do not appear on the chart might still be compatible but have not been tested. All testing has been performed with a stable main supply. The quality of the local main, existing installation and wiring, as well as different manufacturer versions of the above emergency ballasts may affect lamp performance. Since no assurance can be provided regarding these factors, it is a general recommendation to perform a test on-site prior to installing the LED lamps.