

LM-79-08 Test Report

for

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

A21

Model: 17A21G4DIM/840/R

Laboratory: Leading Testing Laboratories

NVLAP CODE: 200960-0

3rd Floor, Bld. 2, NO. 96 Longchuanwu Rd Qianjiang Economy Dev. Zone, Yuhang Dist,
Hangzhou, Zhejiang Province, China 311100


Tel: +86 571 86376106

www.ledtestlab.com

Report No.: HZ18010012f

The laboratory that conducted the testing detailed in this report has been accredited for SSL by NVLAP.

Review by:



Engineer: April Zou
Jan. 08, 2018

Approved by:



Manager: Jim Zhang
Jan. 08, 2018

Note: This report does not imply product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Test Summary

Sample Tested: 17A21G4DIM/840/R

Luminous Efficacy (Lumens /Watt)	Total Luminous Flux (Lumens)	Power (Watts)	Power Factor
129.0	2039.0	15.81	0.9208
CCT (K)	CRI	Stabilization Time (Light & Power)	
4042	85.6	60	

Table 1: Executive Data Summary

Note: The above results are recorded/ derived from measurements made using an Integrating Sphere.

Test specifications:

Date of Receipt : Oct. 30, 2016

Date of Test : Nov. 17, 2016

Test item : Total Luminous Flux, Luminous Distribution Intensity, Luminous Efficacy, Correlated Color Temperature, Color Rendering Index, Chromaticity Coordinate, Electrical parameters

Reference Standard : IESNA LM-79-2008 Approved Method for the Electrical and Photometric Measurements of Solid-State Lighting Products

TABLE OF CONTENT

LM-79-08 Test Report.....	1
Test Summary.....	2
Sample Photos.....	4
TEST RESULTS	5
Goniophotometer Method	6
Spectral Power Distribution - Sphere Spectroradiometer Method	7
Chromaticity Diagram - Sphere Spectroradiometer Method.....	8
Nominal CCT Quadrangles – Sphere Spectroradiometer Method	9
Zonal Lumen Tabulation- Goniophotometer Method	10
Luminous Intensity Distribution Plots- Goniophotometer Method.....	12
Luminous Intensity Data- Goniophotometer Method.....	13
EQUIPMENT LIST	14
TEST METHODS	14
Seasoning of SSL Product.....	14
Sphere-Spectroradiometer Method- Photometric and Electrical Measurements.....	14
Goniophotometer Method	15
Photometric and Electrical Measurements.....	15
Color Characteristics Measurements.....	15
Color Spatial Uniformity	15

Sample Photos




Figure 1- Overview of the sample

Equipment Under Test (EUT)

Name	: A21
Model	: 17A21G4DIM/840/R
Electrical Ratings	: 120V, 60Hz, 17W
Product Description	: 4000K
Manufacturer	: GREEN CREATIVE LTD
Address	: 756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai

TEST RESULTS

Test ambient temperature was 25.0°C.

Base orientation was light down. Test was conducted without a dimmer in the circuit.

The stabilization time of the sample was 60 minutes, and the total operating time including stabilization was 70 minutes.

Sphere-Spectroradiometer Method

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.143
Power Factor	0.9208
Test Power (W)	15.81
THD A%	36.54
Luminous Efficacy (lm/W)	129.0
Total Luminous Flux (lm)	2039.0
Color Rendering Index (CRI)	85.6
R9	21.1
Correlated Color Temperature (CCT)(K)	4042
Chromaticity Chroma x	0.3780
Chromaticity Chroma y	0.3737
Chromaticity Chroma u	0.2247
Chromaticity Chroma v	0.3333
Duv	0.0014
Chromaticity Chroma u'	0.2247
Chromaticity Chroma v'	0.4999

Special Color Rendering Indices	
R1	84.7
R2	93
R3	96.2
R4	83.3
R5	84.7
R6	89.3
R7	86.5
R8	68.2
R9	21.1
R10	82.6
R11	82.5
R12	67.6
R13	87.1
R14	98.5
Rf	84
Rg	95

Table 2: Test data per Sphere-Spectroradiometer Method

Note: According to CIE 1976 (u',v') diagram, $u' = u = 4x/(-2x+12y+3)$, $v' = 3v/2 = 9y/(-2x+12y+3)$.

Goniophotometer Method

Test ambient temperature was 24.4°C.

The photometric distance is 2.47m.

Luminous data was taken at 0.5°vertical intervals and 10°horizontal intervals.

Parameter	Result
Test Voltage (V)	120.0
Voltage frequency (Hz)	60
Test Current (A)	0.147
Power Factor	0.9210
Test Power (W)	16.22
Luminous Efficacy (lm/W)	125.8
Total Luminous Flux (lm)	2040.5
Beam Angle (°)	315.1
Center Beam Candle Power (cd)	150
Spacing Criteria	1.69(0°-180°)/ 1.69(90°-370°)
Zonal Lumens in the 0°-60°Zone	26.31%
Zonal Lumens in the 60°-90°Zone	29.14%
Zonal Lumens in the 90°-120°Zone	26.99%
Zonal Lumens in the 120°-180°Zone	17.56%

Table 3: Test data per Goniophotometer Method

Spectral Power Distribution - Sphere Spectroradiometer Method




Chart 1: Spectral Power Distribution

Spectral Distribution over Visible Wavelength							
WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)	WL(nm)	Radiant(Watts)
380	3.47E-04	485	1.34E-02	590	3.37E-02	695	5.88E-03
385	3.64E-04	490	1.47E-02	595	3.38E-02	700	5.09E-03
390	3.75E-04	495	1.61E-02	600	3.37E-02	705	4.37E-03
395	3.82E-04	500	1.78E-02	605	3.31E-02	710	3.77E-03
400	4.23E-04	505	1.92E-02	610	3.25E-02	715	3.25E-03
405	5.06E-04	510	2.04E-02	615	3.14E-02	720	2.81E-03
410	6.85E-04	515	2.14E-02	620	2.99E-02	725	2.41E-03
415	1.08E-03	520	2.20E-02	625	2.84E-02	730	2.07E-03
420	1.84E-03	525	2.27E-02	630	2.66E-02	735	1.76E-03
425	3.14E-03	530	2.36E-02	635	2.47E-02	740	1.52E-03
430	5.28E-03	535	2.43E-02	640	2.27E-02	745	1.29E-03
435	8.67E-03	540	2.53E-02	645	2.07E-02	750	1.11E-03
440	1.39E-02	545	2.62E-02	650	1.88E-02	755	9.58E-04
445	2.19E-02	550	2.69E-02	655	1.68E-02	760	8.33E-04
450	3.30E-02	555	2.80E-02	660	1.50E-02	765	7.15E-04
455	3.72E-02	560	2.89E-02	665	1.33E-02	770	6.15E-04
460	2.80E-02	565	2.99E-02	670	1.17E-02	775	5.31E-04
465	2.08E-02	570	3.08E-02	675	1.03E-02	780	4.63E-04
470	1.78E-02	575	3.17E-02	680	8.99E-03		
475	1.46E-02	580	3.24E-02	685	7.85E-03		
480	1.30E-02	585	3.32E-02	690	6.81E-03		

Table 4: Spectral Power Distribution Numerical Data per Sphere - Spectroradiometer Method

Chromaticity Diagram - Sphere Spectroradiometer Method




Chart 2: Chromaticity Diagram per Sphere - Spectroradiometer Method

Note: The location on the diagram of the tristimulus coordinates are indicated by the blue diamond.

Nominal CCT Quadrangles – Sphere Spectroradiometer Method




Chart 3: Plot of Lamp x/y coordinates on CIE 1931 Chromaticity Diagram

Zonal Lumen Tabulation- Goniophotometer Method

$\gamma(^{\circ})$	Lumens	% Total
0- 10	14.352	0.70%
10- 20	43.435	2.13%
20- 30	73.517	3.60%
30- 40	104.724	5.13%
40- 50	136.066	6.67%
50- 60	164.694	8.07%
60- 70	187.314	9.18%
70- 80	201.463	9.87%
80- 90	205.907	10.09%
90-100	200.524	9.83%
100-110	186.138	9.12%
110-120	163.98	8.04%
120-130	134.98	6.62%
130-140	100.853	4.94%
140-150	66.431	3.26%
150-160	37.447	1.84%
160-170	16.435	0.81%
170-180	2.241	0.11%
Total	2040.5	100%

$\gamma(^{\circ})$	Lumens	% Total
0-130	1817.094	89.05%
130-180	223.407	10.95%
0-180	2040.5	100%

Table 5: Zonal Lumen Data




Chart 4: Illuminance Plot (Footcandles)

Luminous Intensity Distribution Plots- Goniophotometer Method




Chart 5: Isocandela Plot




Chart 6: Polar Candela Distribution

Luminous Intensity Data- Goniophotometer Method

Table---1 UNIT: cd

C (DEG) y (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150			
5	151	151	151	151	151	150	150	150	149	149	149	149	149	150	150	150			
10	152	153	153	153	152	152	151	150	150	150	149	150	150	151	151	152			
15	155	155	155	155	155	154	152	151	151	151	151	151	151	152	153	154			
20	158	159	159	158	157	156	155	154	153	153	153	153	153	154	155	157			
25	162	163	163	162	161	159	158	157	156	155	155	156	156	157	158	160			
30	166	167	167	166	165	163	161	160	159	159	159	159	159	160	162	164			
35	171	172	172	171	169	167	165	164	163	162	163	163	163	164	166	168			
40	176	177	177	175	174	172	170	169	168	167	167	167	167	168	171	173			
45	180	182	181	180	179	176	174	173	172	172	172	171	171	173	175	178			
50	184	186	186	184	183	181	179	178	177	176	176	176	175	177	179	182			
55	188	190	189	188	186	185	183	182	181	180	180	180	179	180	183	185			
60	190	192	192	190	189	188	186	186	185	184	184	183	182	183	185	188			
65	192	194	193	192	191	190	188	188	188	187	187	186	184	185	187	189			
70	193	195	194	193	192	191	190	190	190	189	189	188	186	186	188	190			
75	192	194	194	193	192	191	191	191	191	190	190	189	187	187	188	190			
80	191	193	193	192	191	191	191	191	191	190	190	189	187	186	188	190			
85	189	191	191	190	189	189	190	190	190	190	190	188	186	185	186	188			
90	187	187	188	188	187	187	188	188	188	188	188	186	184	183	184	185			
95	183	184	184	184	184	185	185	186	186	186	186	184	182	181	181	182			
100	179	179	180	180	180	181	182	182	183	183	183	181	179	177	177	178			
105	174	174	175	175	175	177	178	178	179	180	179	177	175	173	172	174			
110	168	168	169	170	170	172	173	174	174	176	175	172	171	169	167	168			
115	162	161	163	164	164	166	168	168	169	171	169	167	165	163	161	162			
120	154	153	156	156	157	159	161	162	163	165	163	161	159	157	155	155			
125	144	143	147	148	149	151	154	154	156	158	157	154	153	149	145	146			
130	132	131	137	138	139	142	145	146	148	150	148	146	144	140	134	134			
135	119	119	125	127	129	132	135	136	138	140	139	136	134	129	122	121			
140	105	105	113	116	117	121	124	125	127	129	128	126	123	117	108	106			
145	89.6	90.6	99.1	103	105	109	112	113	115	117	116	114	112	105	93.5	90.5			
150	74.3	76.8	85.2	90.5	93.3	96.4	99.3	101	103	104	103	102	99.7	93.4	80.0	75.4			
155	60.6	64.4	71.8	77.9	81.4	84.4	87.2	88.8	90.7	91.1	90.7	89.5	87.7	83.2	68.3	62.3			
160	47.9	52.0	58.3	65.8	70.1	73.2	75.7	77.1	78.7	78.8	78.7	77.7	76.2	73.8	61.0	51.4			
165	38.3	39.5	41.4	51.9	56.2	62.5	65.3	66.4	67.6	67.4	67.5	66.8	64.9	63.5	54.8	43.9			
170	24.0	23.3	23.7	23.7	38.9	48.4	52.1	53.7	54.2	53.8	54.1	52.8	48.4	48.0	42.8	34.7			
175	2.39	4.73	6.27	6.45	11.4	17.1	20.1	21.4	19.3	17.8	15.1	10.2	5.72	3.69	2.05	1.37			
180	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14			

Table 6: Luminous Intensity Data

EQUIPMENT LIST

Test Equipment	Model	Equipment No.	Calibration Date	Calibration Due date
Goniophotometer system	GO-R5000	HZTE011-01	Jul. 27, 2016	Jul. 26, 2017
Digital Power Meter	PF2010A	HZTE028-01	Jul. 27, 2016	Jul. 26, 2017
AC Power Supply	PCR 500L	HZTE001-08	Jul. 27, 2016	Jul. 26, 2017
DC Power Supply	WY12010	HZTE004-03	Jul. 27, 2016	Jul. 26, 2017
Temperature Meter	TES1310	HZTE017-01	Jul. 27, 2016	Jul. 26, 2017
Standard source	D908	HZTE012-01	Jul. 27, 2016	Jul. 26, 2017
Integrate Sphere system	2M	HZTE015-01	Jul. 27, 2016	Jul. 26, 2017
Digital Power Meter	WT210	HZTE008-01	Jul. 27, 2016	Jul. 26, 2017
AC Power Supply	PCR 500L	HZTE001-07	Jul. 27, 2016	Jul. 26, 2017
DC Power Supply	6154	HZTE004-04	Jul. 27, 2016	Jul. 26, 2017
Temperature and humidity recorder	JR900	HZTE018-01	Jul. 27, 2016	Jul. 26, 2017
Standard source	SCL-1400	HZTE012-02	Jul. 27, 2016	Jul. 26, 2017

Table 7: Test Equipment List

TEST METHODS

Seasoning of SSL Product

For the purpose of rating new SSL products, SSL products shall be tested with no seasoning. Therefore, no seasoning was performed.

Sphere-Spectroradiometer Method- Photometric and Electrical Measurements

A Labsphere Model CDS 2100 Spectroradiometer and Two Meter Sphere was used to measure correlated color temperature, chromaticity coordinates, and the color rendering index for each SSL unit. The coating reflectance of each sphere is 98%. The measure geometry is 4π . Self-absorption correction is conducted in testing. Bandwidth of spectroradiometer is 350nm-1050nm.

Ambient temperature was measured at a position inside the sphere. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated FA21 Lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Yokogawa Power Analyzer.

The standard reference of the integrated sphere system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Standards and Technology.

The uncertainty of integrating sphere system reported in this document is expended uncertainty is 2.1% with a coverage factor $k=2$.

Goniophotometer Method

Photometric and Electrical Measurements

An EVERFINE Type C Model GO-R5000 Goniophotometer was used to measure the intensity at each angle of distribution for each sample. The photometric distance is 2.475m for near-field measurement or 30m for far-field measurement. Bandwidth of spectroradiometer is 380nm-780nm.

Ambient temperature was measured at the same height of the sample mounted on the Goniophotometer equipment. Each SSL unit was operated on the client provided driver at the rated input voltage in its designated orientation.

The stabilization time typically ranges from 30 min (small integrated FA21 Lamps) to 2 or more hours for large SSL luminaires). It can be judged that stability is reached when the variation (maximum – minimum) of at least 3 readings of the light output and electrical power over a period of 30 min, taken 15 minutes apart, is less than 0.5 %.

Electrical measurements including voltage, current, and power were measured using the Everfine Digital Power Meter.

Some graphics were created with Photometric Plus software.

The standard reference of the Goniophotometer system is halogen incandescent lamp, the intensity distribution type is omni-directional, and is traceable to the National Institute of Metrology P.R. China.

The uncertainty of goniophotometer system reported in this document is expanded uncertainty is 2.3% with a coverage factor $k=2$.

Color Characteristics Measurements


The color characteristics of SSL products include chromaticity coordinates, correlated color temperature, and color rendering index. These characteristics of SSL products may be spatially non-uniform, and thus, in order that they can be specified accurately, the color quantities shall be measured as values that are spatially average, weighted to intensity, over the angular range where light is intentionally emitted from the SSL product. The color characteristics measurements are using gonio-spectroradiometer.

Color Spatial Uniformity

The characteristics of SSL products may be spatially non-uniform, the chromaticity coordinate shall be measured at two vertical planes ($C=0^\circ/180^\circ$ and $C=90^\circ/270^\circ$) and at 10° or less intervals for vertical angle until the light output dropped to below 10% of the peak intensity. The averaged weighted chromaticity coordinate was calculated from these points. The data was then analyzed to check for delta color differences of the u' , v' chromaticity coordinates. The spatial non-uniformity of chromaticity, $\Delta u'v'$, is determined as the maximum

deviation (distance on the CIE (u' , v') diagram) among all measured points from the spatially averaged chromaticity coordinate.

The geometry for the chromaticity measurement using gonio-spectroradiometer is shown as following.



*** End of Report ***

This report is considered invalidated without the Special Seal for Inspection of the LTL. This report shall not be altered, increased or deleted. The results shown in this test report refer only to the sample(s) tested. Without written approval of LTL, this test report shall not be copied except in full and published as advertisement.