

# IES LM-79-08

## MEASUREMENT AND TEST REPORT

For

### GREEN CREATIVE LTD

Room 3603, Level 36, Tower 1, Enterprise Square Five, 38 Wang Chiu Road, Kowloon Bay, KL, Hong Kong

**Test Model: 25HID/835/277V/E26/R**

<b>Report Type:</b>	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
<b>Test Engineer:</b>	George Yang
<b>Report Number:</b>	PKS200903080-10
<b>Test Date:</b>	2020-09-03 to 2020-09-05
<b>Report Date:</b>	2020-09-07
<b>Reviewed By:</b>	Ray Gao/ EE Engineer
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan). No.248 Chenghu Road, Kunshan, Jiangsu province, China. Tel: +86-0512-86175000 Fax: +86-0512-88934268
<b>Accreditation:</b>	The IAS Accreditation Number TL-749.

## 1. Product Description

### General Information:

One sample was received on 2020-09-03 and used for testing.

Model Tested: 25HID/835/277V/E26/R  
 Manufacturer: GREEN CREATIVE LTD  
 Brand Name: GREEN CREATIVE  
 Product Designation: LED Lamp  
 Burning Time Before Test: 0hour(For New Products)

### Rated Values:

Rated Voltage/Frequency: 120-277VAC 50/60Hz  
 Rated Power: 25W  
 Nominal CCT: 3500K  
 Nominal Lumen Output: 3200lm

## 2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-10-2014: Harmonic Emission Limits – Related Power Quality Requirements for Lighting Equipment
- IES TM-30-18: IES Method for Evaluating Light Source Color Rendition

## 3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
2.0m integrating sphere	EVERFINE	R98	G121960CS1361154D	2019-12-24	2020-12-23
spectroradiometer	EVERFINE	HAAS-2000	M12048CS1361148	2019-12-24	2020-12-23
Digital CC&CV DC Power Supply	EVERFINE	WY305	G115986CN1361134	2019-12-20	2020-12-19
Temperature/humidity/clock	KEJIAN	TA298	EE053	2019-12-02	2020-12-01
Standard Light Source	INVENTFINE	N/A	JWWCR020106	2019-11-19	2020-11-18
Digital Power Meter	YOKOGAWA	WT210	91KB35700	2020-04-02	2021-04-01
Intelligence ac power supply	EVERFINE	DPS1005	G119890CS1361121	2020-04-02	2021-04-01
AC Power Supply	INVENTFINE	CHP-5KVA	900511765	2020-04-02	2021-04-01
DC Power Supply	INVENTFINE	WL3010	JWDMP030001	2019-12-20	2020-12-19
Power Meter	INVENTFINE	WT500	GSQSQ200007	2020-04-02	2021-04-01
Goniophotometer	INVENTFINE	GPM-1900	YWGCF120001	2020-01-22	2021-01-21
Wireless Weather Station	ZHONGXING	KG218	N/A	2019-12-02	2020-12-01
Standard Light Source	INVENTFINE	N/A	JWBYR040008	2020-03-19	2021-03-18

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

## 4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$  during measurement. And relative humidity is less than 65%.

### Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

$4\pi$  geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is  $U_{\text{rel}}=2.70\%$  ( $k=2$ ), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is  $U=27\text{K}$  ( $k=2$ ), at the 95% confidence level. The uncertainty of the CRI is  $U=2.7(k=2)$ , at the 95% confidence level.

The uncertainty of power meter AC current  $U_{\text{rel}}=0.27\%$  of rdg, AC Voltage  $U_{\text{rel}}=0.26\%$  of rdg, Power  $U_{\text{rel}}=0.41\%$  ( $k=2$ ), at the 95% confidence level.

### Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle ( $\gamma$ ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous flux is  $U_{\text{rel}}=2.6\%$  ( $k=2$ ), at the 95% confidence level.

### Fidelity Index and Gamut Index Calculation

The  $R_i$ ,  $R_g$  was calculated according to IES TM-30-18 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

## 5. Test Result

### [Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Downward**


### Photometric and Electrical Measurement Result







Voltage(V)	Frequency(Hz)	Current(A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy(lm/W)
119.9	60	0.209	24.88	0.9927	3620.5	145.49

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
11.250	3487	-0.0029	0.4030	0.3831	0.2374	0.5077


### Color Rendering Index

<b>Ra</b>			
<b>85.3</b>			
<b>R1</b>	<b>R2</b>	<b>R3</b>	<b>R4</b>
85	95	95	83
<b>R5</b>	<b>R6</b>	<b>R7</b>	<b>R8</b>
85	92	83	64
<b>R9</b>	<b>R10</b>	<b>R11</b>	<b>R12</b>
18	87	82	72
<b>R13</b>	<b>R14</b>	<b>R15</b>	
88	98	79	






### Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	1.336E+00	421	2.606E+00	462	4.296E+01	503	2.988E+01	544	4.421E+01
381	1.391E+00	422	2.961E+00	463	4.056E+01	504	3.044E+01	545	4.449E+01
382	1.222E+00	423	3.250E+00	464	3.869E+01	505	3.107E+01	546	4.490E+01
383	1.025E+00	424	3.644E+00	465	3.714E+01	506	3.163E+01	547	4.516E+01
384	1.019E+00	425	4.017E+00	466	3.581E+01	507	3.220E+01	548	4.557E+01
385	8.920E-01	426	4.466E+00	467	3.467E+01	508	3.264E+01	549	4.601E+01
386	7.717E-01	427	4.948E+00	468	3.372E+01	509	3.310E+01	550	4.640E+01
387	8.869E-01	428	5.458E+00	469	3.265E+01	510	3.355E+01	551	4.675E+01
388	6.128E-01	429	6.042E+00	470	3.158E+01	511	3.399E+01	552	4.715E+01
389	7.423E-01	430	6.670E+00	471	3.041E+01	512	3.451E+01	553	4.763E+01
390	7.594E-01	431	7.337E+00	472	2.924E+01	513	3.496E+01	554	4.800E+01
391	7.641E-01	432	8.046E+00	473	2.811E+01	514	3.530E+01	555	4.847E+01
392	6.540E-01	433	8.856E+00	474	2.682E+01	515	3.572E+01	556	4.880E+01
393	5.456E-01	434	9.816E+00	475	2.558E+01	516	3.604E+01	557	4.939E+01
394	5.606E-01	435	1.081E+01	476	2.459E+01	517	3.638E+01	558	4.995E+01
395	5.763E-01	436	1.190E+01	477	2.353E+01	518	3.669E+01	559	5.054E+01
396	6.309E-01	437	1.318E+01	478	2.286E+01	519	3.708E+01	560	5.095E+01
397	4.795E-01	438	1.438E+01	479	2.235E+01	520	3.728E+01	561	5.150E+01
398	4.482E-01	439	1.593E+01	480	2.193E+01	521	3.768E+01	562	5.188E+01
399	5.439E-01	440	1.750E+01	481	2.155E+01	522	3.789E+01	563	5.256E+01
400	5.238E-01	441	1.943E+01	482	2.140E+01	523	3.825E+01	564	5.302E+01
401	5.551E-01	442	2.147E+01	483	2.145E+01	524	3.855E+01	565	5.353E+01
402	5.163E-01	443	2.366E+01	484	2.150E+01	525	3.879E+01	566	5.426E+01
403	5.282E-01	444	2.613E+01	485	2.168E+01	526	3.897E+01	567	5.488E+01
404	5.448E-01	445	2.908E+01	486	2.194E+01	527	3.939E+01	568	5.530E+01
405	5.822E-01	446	3.245E+01	487	2.213E+01	528	3.956E+01	569	5.583E+01
406	6.357E-01	447	3.580E+01	488	2.243E+01	529	3.990E+01	570	5.643E+01
407	6.855E-01	448	3.973E+01	489	2.270E+01	530	4.018E+01	571	5.707E+01
408	7.335E-01	449	4.373E+01	490	2.306E+01	531	4.035E+01	572	5.761E+01
409	7.576E-01	450	4.751E+01	491	2.345E+01	532	4.062E+01	573	5.825E+01
410	8.487E-01	451	5.127E+01	492	2.383E+01	533	4.086E+01	574	5.885E+01
411	9.032E-01	452	5.430E+01	493	2.422E+01	534	4.118E+01	575	5.943E+01
412	9.784E-01	453	5.660E+01	494	2.471E+01	535	4.151E+01	576	5.997E+01
413	1.074E+00	454	5.805E+01	495	2.530E+01	536	4.175E+01	577	6.058E+01
414	1.194E+00	455	5.843E+01	496	2.566E+01	537	4.194E+01	578	6.121E+01
415	1.382E+00	456	5.787E+01	497	2.637E+01	538	4.222E+01	579	6.172E+01
416	1.508E+00	457	5.622E+01	498	2.687E+01	539	4.248E+01	580	6.219E+01
417	1.740E+00	458	5.394E+01	499	2.753E+01	540	4.284E+01	581	6.272E+01
418	1.932E+00	459	5.135E+01	500	2.814E+01	541	4.320E+01	582	6.327E+01
419	2.127E+00	460	4.847E+01	501	2.875E+01	542	4.344E+01	583	6.382E+01
420	2.360E+00	461	4.562E+01	502	2.929E+01	543	4.380E+01	584	6.432E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	6.488E+01	626	5.827E+01	667	2.539E+01	708	7.647E+00	749	2.189E+00
586	6.514E+01	627	5.765E+01	668	2.467E+01	709	7.419E+00	750	2.146E+00
587	6.571E+01	628	5.681E+01	669	2.410E+01	710	7.152E+00	751	2.081E+00
588	6.600E+01	629	5.604E+01	670	2.341E+01	711	6.974E+00	752	2.046E+00
589	6.641E+01	630	5.530E+01	671	2.271E+01	712	6.773E+00	753	1.988E+00
590	6.680E+01	631	5.450E+01	672	2.219E+01	713	6.571E+00	754	1.941E+00
591	6.709E+01	632	5.367E+01	673	2.161E+01	714	6.335E+00	755	1.861E+00
592	6.738E+01	633	5.295E+01	674	2.094E+01	715	6.153E+00	756	1.815E+00
593	6.766E+01	634	5.201E+01	675	2.038E+01	716	6.022E+00	757	1.772E+00
594	6.785E+01	635	5.105E+01	676	1.988E+01	717	5.785E+00	758	1.729E+00
595	6.822E+01	636	5.024E+01	677	1.930E+01	718	5.635E+00	759	1.712E+00
596	6.844E+01	637	4.937E+01	678	1.880E+01	719	5.432E+00	760	1.657E+00
597	6.842E+01	638	4.863E+01	679	1.827E+01	720	5.323E+00	761	1.635E+00
598	6.858E+01	639	4.776E+01	680	1.779E+01	721	5.194E+00	762	1.609E+00
599	6.869E+01	640	4.675E+01	681	1.720E+01	722	4.982E+00	763	1.548E+00
600	6.864E+01	641	4.602E+01	682	1.674E+01	723	4.828E+00	764	1.516E+00
601	6.866E+01	642	4.510E+01	683	1.627E+01	724	4.703E+00	765	1.478E+00
602	6.865E+01	643	4.426E+01	684	1.583E+01	725	4.567E+00	766	1.405E+00
603	6.859E+01	644	4.346E+01	685	1.532E+01	726	4.399E+00	767	1.388E+00
604	6.848E+01	645	4.245E+01	686	1.492E+01	727	4.302E+00	768	1.364E+00
605	6.844E+01	646	4.170E+01	687	1.444E+01	728	4.169E+00	769	1.311E+00
606	6.825E+01	647	4.079E+01	688	1.405E+01	729	4.001E+00	770	1.308E+00
607	6.805E+01	648	3.999E+01	689	1.360E+01	730	3.889E+00	771	1.247E+00
608	6.776E+01	649	3.916E+01	690	1.326E+01	731	3.758E+00	772	1.242E+00
609	6.752E+01	650	3.830E+01	691	1.287E+01	732	3.623E+00	773	1.199E+00
610	6.717E+01	651	3.742E+01	692	1.248E+01	733	3.561E+00	774	1.190E+00
611	6.682E+01	652	3.660E+01	693	1.212E+01	734	3.460E+00	775	1.149E+00
612	6.643E+01	653	3.581E+01	694	1.172E+01	735	3.334E+00	776	1.107E+00
613	6.606E+01	654	3.498E+01	695	1.141E+01	736	3.251E+00	777	1.100E+00
614	6.560E+01	655	3.411E+01	696	1.116E+01	737	3.192E+00	778	1.119E+00
615	6.523E+01	656	3.340E+01	697	1.074E+01	738	3.072E+00	779	1.121E+00
616	6.470E+01	657	3.251E+01	698	1.039E+01	739	2.935E+00	780	1.123E+00
617	6.418E+01	658	3.185E+01	699	1.007E+01	740	2.876E+00		
618	6.356E+01	659	3.098E+01	700	9.808E+00	741	2.772E+00		
619	6.303E+01	660	3.025E+01	701	9.512E+00	742	2.693E+00		
620	6.236E+01	661	2.959E+01	702	9.264E+00	743	2.626E+00		
621	6.178E+01	662	2.885E+01	703	8.960E+00	744	2.576E+00		
622	6.123E+01	663	2.816E+01	704	8.688E+00	745	2.455E+00		
623	6.053E+01	664	2.737E+01	705	8.362E+00	746	2.413E+00		
624	5.986E+01	665	2.671E+01	706	8.150E+00	747	2.328E+00		
625	5.902E+01	666	2.604E+01	707	7.881E+00	748	2.258E+00		

CIE 1931xy Chromaticity Diagram



7-Step Chromaticity Quadrangles





### [Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0hour**

Test orientation: **Downward**


### Electrical Measurement

Input Voltage(V)	Frequency(Hz)	Input Current(A)	Power (W)	Power Factor
120.0	60	0.209	24.96	0.996

### Photometric Measurement

Luminous Flux(lm)	Efficacy(lm/W)	$I_{max}(cd)$	S/MH(C0/180)	S/MH(C90/270)
3618.2	145.01	366.2	1.67	1.66

### Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle(50% $I_{max}$ ):	280.3	278.9	279.2	281.0	279.9
Field Angle(10% $I_{max}$ ):	346.8	346.4	347.7	348.5	347.4

**Luminous Intensity (cd) Distribution Data**

C y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	315.2	315.2	315.2	315.2	315.2	315.2	315.2	315.2
5.0°	314.9	314.2	314.2	313.8	314.4	315.3	315.6	315.8
10.0°	315.2	314.5	313.8	314.5	315.7	316.0	317.5	318.4
15.0°	317.0	316.1	315.7	316.2	317.3	318.7	321.4	322.5
20.0°	320.3	318.8	318.0	319.0	320.4	322.5	325.1	326.0
25.0°	324.5	322.7	322.1	322.8	324.2	326.5	329.5	331.5
30.0°	329.7	327.0	326.4	326.5	328.5	330.4	333.9	336.7
35.0°	334.4	331.9	331.0	331.7	333.6	335.3	339.8	341.9
40.0°	339.8	337.4	336.0	336.3	337.3	340.3	343.3	346.8
45.0°	344.5	341.5	340.0	340.7	340.7	343.1	347.1	350.6
50.0°	348.6	345.4	343.2	342.7	343.9	344.2	349.1	351.8
55.0°	350.9	347.9	345.1	344.2	344.8	345.2	349.4	353.8
60.0°	351.4	349.5	345.9	344.8	345.9	345.8	350.0	352.0
65.0°	352.1	348.7	345.0	343.3	343.8	343.6	346.9	349.1
70.0°	350.0	347.5	343.4	341.2	340.4	339.2	344.7	346.2
75.0°	346.4	343.7	339.5	337.8	336.4	335.3	340.0	341.0
80.0°	342.5	341.0	335.5	332.6	331.4	329.1	332.5	334.6
85.0°	336.6	334.8	329.9	326.8	326.2	321.8	326.1	327.4
90.0°	329.2	328.2	322.4	319.6	318.0	313.6	317.8	319.1
95.0°	321.4	319.9	314.6	311.0	308.6	305.1	307.0	309.0
100.0°	310.8	310.4	305.2	301.5	297.8	294.4	296.6	296.4
105.0°	300.4	299.6	294.3	290.0	286.8	282.7	283.8	285.1
110.0°	287.5	287.3	282.4	278.2	274.4	270.5	270.2	269.9
115.0°	274.7	273.8	269.0	263.3	260.8	256.1	256.0	256.2
120.0°	259.5	258.5	254.5	251.4	246.2	242.1	241.1	240.5
125.0°	244.9	243.4	239.8	234.5	231.5	225.9	223.9	223.5
130.0°	228.1	226.7	223.0	219.1	213.7	209.3	207.6	206.5
135.0°	210.1	209.4	206.2	201.9	196.9	191.8	190.2	188.4
140.0°	192.0	190.8	187.7	183.4	178.5	172.9	171.9	169.8
145.0°	174.1	172.1	168.9	164.2	159.8	154.4	152.4	150.2
150.0°	154.9	153.0	149.4	144.7	139.4	135.1	132.3	130.4
155.0°	135.6	134.3	130.4	125.3	119.5	115.0	112.4	110.8
160.0°	113.5	115.1	110.3	105.6	100.8	96.3	93.6	92.0
165.0°	92.8	92.2	84.7	86.7	84.0	79.6	76.0	75.1
170.0°	65.6	64.4	58.2	61.2	64.5	57.2	49.3	48.9
175.0°	26.8	20.2	22.5	19.7	24.0	26.8	20.7	21.2
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Luminous Intensity (cd) Distribution Data (cont.)

C y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	315.2	315.2	315.2	315.2	315.2	315.2	315.2	315.2
5.0°	318.7	318.1	317.6	317.5	317.3	316.3	315.9	314.9
10.0°	321.1	321.7	321.8	321.2	320.1	318.4	317.6	315.6
15.0°	326.9	326.6	326.7	325.7	324.6	323.0	319.6	318.0
20.0°	331.5	332.5	332.7	331.6	329.7	326.8	324.4	321.8
25.0°	338.3	338.2	339.0	338.2	335.3	332.5	329.3	324.8
30.0°	344.4	345.5	345.7	344.4	341.7	337.8	335.1	331.6
35.0°	349.5	351.8	352.2	351.4	348.1	344.9	340.8	336.8
40.0°	355.7	357.6	357.9	356.5	353.6	349.1	346.4	342.2
45.0°	358.4	361.2	362.0	361.2	358.2	353.4	350.4	347.9
50.0°	361.2	364.3	365.3	364.3	361.5	358.0	355.0	351.8
55.0°	361.6	365.0	366.2	365.7	363.6	358.6	356.5	353.2
60.0°	360.9	365.0	365.9	365.3	363.7	359.4	357.8	354.3
65.0°	357.4	362.2	363.4	363.5	361.7	357.9	357.2	354.2
70.0°	353.4	358.2	359.6	359.7	358.5	354.8	355.1	352.6
75.0°	346.5	352.1	353.0	354.9	353.9	350.2	350.9	348.6
80.0°	340.4	345.6	346.1	347.2	347.1	344.1	345.6	343.4
85.0°	333.0	336.4	337.0	339.3	338.3	336.5	339.4	336.9
90.0°	321.2	325.9	326.6	328.1	328.9	327.3	329.6	328.6
95.0°	310.3	314.3	315.8	317.7	318.6	317.7	320.1	319.8
100.0°	298.2	301.1	302.7	305.3	306.4	306.0	309.9	307.8
105.0°	284.2	288.3	289.9	292.7	293.1	293.7	296.1	296.9
110.0°	270.8	273.4	275.4	277.3	279.4	280.8	283.4	284.2
115.0°	255.6	257.6	260.0	263.3	265.6	266.9	270.1	270.5
120.0°	240.4	243.5	244.9	248.3	251.3	253.0	255.9	257.1
125.0°	223.8	227.2	228.9	232.1	235.0	237.4	241.2	242.2
130.0°	206.7	208.2	210.9	215.1	218.8	221.7	224.6	226.1
135.0°	189.0	191.3	192.7	196.6	201.1	203.9	206.9	209.2
140.0°	170.0	172.4	174.6	178.4	182.4	185.7	190.0	190.4
145.0°	151.1	153.0	155.3	159.5	163.6	166.8	171.1	171.9
150.0°	130.9	133.0	135.5	139.8	145.0	148.2	152.1	154.0
155.0°	111.2	112.2	115.9	120.2	125.2	129.1	132.4	134.7
160.0°	92.6	93.3	96.7	100.7	105.4	109.5	112.1	114.1
165.0°	74.8	76.2	79.7	82.6	86.8	90.8	93.2	90.6
170.0°	53.4	56.9	60.1	64.2	68.7	72.8	74.0	67.9
175.0°	24.8	22.9	25.7	26.7	30.9	39.1	46.6	39.5
180.0°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

**Zonal Lumen Density Measurement**

Deg	Flux (lm)	%
0-5	7.5	0.21
5-10	22.7	0.63
10-15	37.9	1.05
15-20	53.2	1.47
20-25	68.7	1.90
25-30	84.2	2.33
30-35	99.6	2.75
35-40	114.6	3.17
40-45	128.9	3.56
45-50	142.1	3.93
50-55	153.9	4.25
55-60	164.0	4.53
60-65	172.1	4.76
65-70	178.1	4.92
70-75	181.9	5.03
75-80	183.4	5.07
80-85	182.8	5.05
85-90	179.9	4.97
90-95	174.8	4.83
95-100	167.8	4.64
100-105	159.0	4.39
105-110	148.7	4.11
110-115	137.1	3.79
115-120	124.7	3.45
120-125	111.6	3.08
125-130	97.9	2.70
130-135	84.0	2.32
135-140	70.3	1.94
140-145	57.1	1.58
145-150	44.8	1.24
150-155	33.6	0.93
155-160	23.7	0.66
160-165	15.4	0.43
165-170	8.7	0.24
170-175	3.2	0.09
175-180	0.3	0.01

Deg	Flux (lm)	%
0-5	7.5	0.21
0-10	30.2	0.83
0-15	68.1	1.88
0-20	121.3	3.35
0-25	190.0	5.25
0-30	274.2	7.58
0-35	373.8	10.33
0-40	488.4	13.50
0-45	617.3	17.06
0-50	759.4	20.99
0-55	913.3	25.24
0-60	1077.2	29.77
0-65	1249.3	34.53
0-70	1427.4	39.45
0-75	1609.3	44.48
0-80	1792.8	49.55
0-85	1975.6	54.60
0-90	2155.5	59.57
0-95	2330.3	64.40
0-100	2498.1	69.04
0-105	2657.1	73.44
0-110	2805.8	77.55
0-115	2942.9	81.34
0-120	3067.6	84.78
0-125	3179.2	87.87
0-130	3277.1	90.57
0-135	3361.1	92.89
0-140	3431.4	94.84
0-145	3488.5	96.42
0-150	3533.3	97.65
0-155	3566.9	98.58
0-160	3590.6	99.24
0-165	3606.0	99.66
0-170	3614.7	99.90
0-175	3617.8	99.99
0-180	3618.2	100.00

## 6. Product Photo



## Directions

1. The information marked "superscript #" is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
2. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
3. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of the Company.
6. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

\*\*\*\*\*END OF REPORT\*\*\*\*\*