

# IESNA LM-79: 2008

## Measurement and Test Report

for

### Green Creative Ltd.

Room 1206-7, New Victory House, 93-103 Wing Lok Street, Central, HONG KONG

Aug 24, 2015

|                              |  |
|------------------------------|--|
| <b>Product Name:</b>         | LED  |
| <b>Model No:</b>             | 22TRMG4DIM/927/W/H ; 22TRMG4DIM/927/B/H ;<br>22TRMG4DIM/927/W/J; 22TRMG4DIM/927/B/J;<br>22TRMG4DIM/927/W/L; 22TRMG4DIM/927/B/L   |
| <b>Test Engineer:</b>        | David Zhang  |
| <b>Report No.:</b>           | BTR66.181.15.0002.21-4    |
| <b>Sample Received Date:</b> | Feb 06, 2015   |
| <b>Test Performed Date:</b>  | Feb 06, 2015 to Mar 17, 2015   |
| <b>Reviewed By:</b>          | Steven Hsu   |
| <b>Prepared By:</b>          | <b>BEST Test Service Shenzhen Co., Ltd.</b><br>1st Floor, 1st Building, Weitai Industrial Park, Yingrenshi, Shiyan,<br>Baoan, Shenzhen, China<br>TEL: +86-755-28236006<br>FAX: +86-755-23467087-811<br>Email: <a href="mailto:certification@bestcert.cn">certification@bestcert.cn</a> |



**Note:** This report is not valid as a BEST Test Report unless signed by an approved BEST Test Service Shenzhen Co., Ltd. This report shall not be reproduced except in full without the written approval of the testing laboratory. The test report only allows to be revised within the retention period unless further standard or the requirement was noticed. This report is for the exclusive use of BEST's Client and is provided pursuant to the agreement between BEST and its Client. BEST's responsibility and Liability are limited to the terms and conditions of the agreement. BEST assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the BEST name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by BEST. The observations and test results in this report are relevant only to the sample tested. This report by itself does not cover that the material, product, of service is or has ever been under a BEST certification program. National Voluntary Laboratory Accreditation Program (NVLAP) has accredited this laboratory under ISO17025: 2005 for specific laboratory activities as listed in the NVLAP directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation. This report must not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the U.S. Government.

**TABLE OF CONTENTS**

|   |           |
|---|-----------|
| <b>1 - GENERAL INFORMATION.....</b>   | <b>3</b>  |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                  | 3         |
| 1.2 OBJECTIVE .....   | 3         |
| 1.3 TEST FACILITY DESCRIPTION.....  | 4         |
| 1.4 TEST EQUIPMENT LIST .....   | 4         |
| <b>2 - TEST METHOD.....</b>   | <b>5</b>  |
| 2.1 PHOTOMETRIC AND ELECTRICAL MEASUREMENT (INTEGRATED SPHERE METHOD) .....   | 5         |
| 2.2 PHOTOMETRIC AND ELECTRICAL MEASUREMENT (GONIOPHOTOMETER METHOD) .....     | 5         |
| 2.3 DEVIATION FROM STANDARD OPERATING PROCEDURE .....                         | 5         |
| <b>3 – SUMMARY OF TEST RESULT .....</b>                                       | <b>6</b>  |
| <b>4 – SPECTRAL FLUX PLOTS .....</b>  | <b>8</b>  |
| <b>5 – EUT PHOTOS.....</b>  | <b>9</b>  |
| <b>6 – LUMINOUS INTENSITY DISTRIBUTION TEST PLOTS (CIE CHROMATICITY).....</b> | <b>10</b> |



## 1 - GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

|   |   |
|---|---|
| Applicant   | : Green Creative Ltd.   |
| Product Name  | : LED   |
| Model No  | : 22TRMG4DIM/927/W/H; 22TRMG4DIM/927/B/H ;<br>22TRMG4DIM/927/W/J; 22TRMG4DIM/927/B/J;<br>22TRMG4DIM/927/W/L; 22TRMG4DIM/927/B/L |
| Brand   | : GREEN CREATIVE  |
| Nominal Operation Voltage                                       | : AC 120V/60Hz  |
| Nominal Power   | : 22W   |
| Nominal CCT   | : 2700K   |
| Nominal CRI   | : 90  |
| Nominal Lumen Output  | : 1200 Lumens   |
| Nominal Life Time   | : 40000 Hours   |
| Number of hours operated prior to measurement for new sample    | : 0 Hours   |
| Stabilization Time  | : 1.5 hours   |
| Total operating time for measurement include stabilization time | : 3.5 hours   |
| Date of Receiving Sample  | : Feb 06, 2015  |
| Measurement quantities measured                                 | : 1 pcs   |
| Orientation During Testing                                      | : Base up   |
| Test Requested  | : Electrical and Photometric Test<br>Luminous Intensity Distribution Test   |

Note: These models are only color and lamp base different, here we choose 22TRMG4DIM/927/W/H to be tested and others to share the test data.

### 1.2 Objective

The following test report is prepared on behalf of Green Creative Ltd. in accordance with IESNA LM-79-08, used the following American National Standards or Illumination Engineering Society of North America test guides:

ANSI C78.377-2008: Specifications for the Chromaticity of Solid State Lighting Products;

ANSI C79.1- 2002: American National Standard for Electric Lamps – Nomenclature for Glass Bulbs Intended for Use with Electric Lamps;

ANSI C78.20 – 2003: American National Standard for Electric Lamps – A, G, PS, and Similar Shapes with E26 Medium Screw Bases;

ANSI C78.21 – 2011: American National Standard for Electric Lamps – PAR and R Shapes;

ANSI C78.24 – 2001: American National Standard for Electric Lamps – Two-inch (51 mm);

Integral-reflector Lamps with Front Covers and GU5.3 or GX 5.3 Bases;

ANSI/IEC C81.61-2003: American National Standard for Electric Lamp Bases;

ANSI/IEEE C62.41 – 1991 (01-May-1991): Surge Voltages in Low-Voltage AC Power Circuits, Recommended Practice for;

CIE Publication No. 13.3 – 1995: Method of Measuring and Specifying Color Rendering of Light Sources;

CIE Publication No. 18.2 – 1983: The Basis of Physical Photometry;

IESNA LM-16-1993: Practical Guide to Colorimetry of Light Sources;

IESNA LM-28-89 – 1989: Guide for the Selection, Care, and Use of Electrical Instruments in the Photometric Laboratory;

IESNA LM-79-08 Electrical and Photometric Measurement of Solid State Lighting Products

UL 1993 – 1999: Standard for Self-Ballasted Lamps and Lamp Adapters;

UL 8750 – 2009: Light Emitting Diode (LED) Equipment for Use in Lighting Products.

### 1.3 Test Facility Description

The Energy Efficiency Lab used by BEST to collect energy efficiency measurement data is located in 1st Floor, 1st Building, Weitai Industrial Park, Yingrenshi, Shiyao, Baoan, Shenzhen, China. BEST Test Service Shenzhen Co., Ltd is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200770-0). BEST Test Service Shenzhen Co., Ltd is also an ELI accredited lab for lighting products (ELI Certificate No. ELI-L04-2010) and UL accredited lab for lighting products

### 1.4 Test Equipment List

| Apparatus List | Device                                    | Cal. Date    | Cal Due Date |
|----------------|---|--------------|--------------|
| 1              | Integral Sphere+ Spectrophotometer System | Mar 10, 2015 | Mar 09, 2016 |
| 2              | Digital Power Meter                       | Oct 18, 2014 | Oct 17, 2015 |
| 3              | Goniophotometer+ Spectrophotometer System | Nov 20, 2014 | Nov 19, 2015 |
| 4              | Standard Light Source                     | Sep 17, 2014 | Sep 16, 2015 |
| 5              | Standard Light Source                     | Sep 17, 2014 | Sep 16, 2015 |
| 6              | Digital Storage Oscilloscope              | Oct 18, 2014 | Oct 17, 2015 |
| 7              | Ultra Compact Simulator                   | Oct 20, 2014 | Oct 19, 2015 |
| 8              | Temperature Chamber                       | Oct 20, 2014 | Oct 19, 2015 |
| 9              | Digital Caliper                           | Nov 20, 2014 | Nov 19, 2015 |
| 10             | Digital CC&CV DC Power Supply(30V 5A)     | N/A          | N/A          |
| 11             | 5 1/2 Digital Multimeter                  | Oct 18, 2014 | Oct 17, 2015 |
| 12             | Digital CC&CV DC Power Supply(120V 10A)   | N/A          | N/A          |
| 13             | 6 1/2 Digital Multimeter                  | Oct 18, 2014 | Oct 17, 2015 |
| 14             | Digital Multimeter                        | Oct 18, 2014 | Oct 17, 2015 |
| 15             | Temperature Recorder+Thermocouple         | Nov 20, 2014 | Nov 19, 2015 |
| 16             | Timer Controller                          | Nov 20, 2014 | Nov 19, 2015 |

**Statement of Traceability:** BEST Test Service Shenzhen Co., Ltd. certifies that all calibration has been performed using suitable standards traceable to the NIM China.

## 2 - Test Method

### 2.1 Photometric and Electrical Measurement (Integrated Sphere Method)

Total light output (luminous flux) for the  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$  ambient temperature conditions is measured using a 1.6m  $\Phi$  geometry integrating sphere. Temperature is measured at a position inside the sphere. Spectral radiant flux measurements are made using Lab sphere to the detector port of the integrating sphere. Each lamp is operated at rated voltage in its designated orientation. Each lamp should be stable before measurements are made. The determining method of stable is as follows:

Step 1 Take 3 measurements of the lamp light output at 15 minute interval (total time=30minutes.) This time period is in addition to the recommended pre-burning time.

Step 2 Calculate the percent difference between the maximum measured value and the minimum measured value for the three consecutive measurements.

Step 3 If the value calculated in Step 2 does not exceed 0.5 percent, the lamp is considered stable. Luminous flux, chromaticity coordinates, correlated color temperature and color rendering index for each lamp are calculated from the spectral radiant flux measurements taken at 2 nm intervals over the range 350 to 1050 nm. The calibration of the sphere photometer-spectrometer system is traceable to the NIST USA. Lamp efficacy (lumens per watts) for each lamp model is computed based on the revised luminous flux result. Electrical measurements including voltage, current, power and power factor are measured using the digital power Meter.

The total uncertainty of the light output measurements is estimated, at the 95% confidence level, not to exceed  $\pm 1.12\%$  over the wavelength range 350-1050 nm.

### 2.2 Photometric and Electrical Measurement (Goniophotometer Method)

A Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample; the photometric distance is 24m. Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to be stable before measurement was made. Electrical measurements including voltage, current, power and power factor were measured using the Power Analyzer

Before each measurement, the method below should be used to determine the lamp is stable or not.

Step 1 Take 3 measurements of the lamp intensity at 15 minute interval (total time=30minutes.) This time period is in addition to the recommended pre-burning time.

Step 2 Calculate the percent difference between the maximum measured value and the minimum measured value for the three consecutive measurements.

Step 3 If the value calculated in Step 2 does not exceed 0.5 percent, the lamp is considered stable.

Some graphics were created with Photometric Plus software.

### 2.3 Deviation from standard operating procedure

None.


### 3 – Summary of Test Result

|                 | Item                               | Test Result                            |                             | Accreditation |
|-----------------|------------------------------------|--|-----------------------------|---------------|
| Required Fields | Lumen Output (Lumens)              | 1502.27                                |                             | NVLAP/EPA     |
|                 | Luminous Efficacy (lm/w)           | 70.30                                  |                             | NVLAP/EPA     |
|                 | Correlated Color Temperature (CCT) | 2727                                   |                             | NVLAP/EPA     |
|                 | Color Rendering Index– CRI         | 90.0                                   |                             | NVLAP/EPA     |
|                 | Input Power (W)                    | 21.36                                  |                             | NVLAP/EPA     |
| Optional Fields | Power Type                         | <input checked="" type="checkbox"/> AC | <input type="checkbox"/> DC | /             |
|                 | Input Voltage (V)                  | 120.0                                  |                             | NVLAP/EPA     |
|                 | Input Current (A)                  | 0.1820                                 |                             | NVLAP/EPA     |
|                 | Power Factor                       | 0.9768                                 |                             | NVLAP/EPA     |
|                 | x(CIE 1931)                        | 0.4575                                 |                             | NVLAP/EPA     |
|                 | y(CIE 1931)                        | 0.4097                                 |                             | NVLAP/EPA     |
|                 | u' (CIE 1976)                      | 0.2613                                 |                             | NVLAP/EPA     |
|                 | v' (CIE 1976)                      | 0.5267                                 |                             | NVLAP/EPA     |
|                 | Duv(CIE 1976)                      | 0.0001                                 |                             | NVLAP/EPA     |
|                 | Beam Angle (Degree)                | 20.9                                   |                             | NVLAP/EPA     |
|                 | Center beam candlepower (cd)       | 7761                                   |                             | NVLAP/EPA     |
|                 | Zonal lumen density (0-60°)        | 97.9%                                  |                             | NVLAP/EPA     |
|                 | Zonal lumen density (60-90°)       | 2.1%                                   |                             | NVLAP/EPA     |
|                 | Zonal lumen density (90-120°)      | 0.0%                                   |                             | NVLAP/EPA     |
|                 | Zonal lumen density (120-180°):    | 0.0%                                   |                             | NVLAP/EPA     |

|  |           |    |           |
|--|-----------|----|-----------|
|  | CRI (R1)  | 90 | NVLAP/EPA |
|  | CRI (R2)  | 97 | NVLAP/EPA |
|  | CRI (R3)  | 96 | NVLAP/EPA |
|  | CRI (R4)  | 88 | NVLAP/EPA |
|  | CRI (R5)  | 90 | NVLAP/EPA |
|  | CRI (R6)  | 97 | NVLAP/EPA |
|  | CRI (R7)  | 87 | NVLAP/EPA |
|  | CRI (R8)  | 74 | NVLAP/EPA |
|  | CRI (R9)  | 47 | NVLAP/EPA |
|  | CRI (R10) | 93 | NVLAP/EPA |
|  | CRI (R11) | 88 | NVLAP/EPA |
|  | CRI (R12) | 85 | NVLAP/EPA |
|  | CRI (R13) | 92 | NVLAP/EPA |
|  | CRI (R14) | 98 | NVLAP/EPA |

| [OTHER] | Gamma(deg) | Fz(lm) | Ft(lm)  | %Lum   | %Lamp  |
|---------|------------|--------|---------|--------|--------|
| [OTHER] | 0- 10      | 549.30 | 549.30  | 36.57  | 36.57  |
| [OTHER] | 10- 20     | 574.94 | 1124.25 | 74.84  | 74.84  |
| [OTHER] | 20- 30     | 221.17 | 1345.41 | 89.56  | 89.56  |
| [OTHER] | 30- 40     | 67.08  | 1412.49 | 94.02  | 94.02  |
| [OTHER] | 40- 50     | 31.79  | 1444.28 | 96.14  | 96.14  |
| [OTHER] | 50- 60     | 27.14  | 1471.42 | 97.95  | 97.95  |
| [OTHER] | 60- 70     | 20.94  | 1492.36 | 99.34  | 99.34  |
| [OTHER] | 70- 80     | 8.92   | 1501.28 | 99.93  | 99.93  |
| [OTHER] | 80- 90     | 0.96   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 90-100     | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 100-110    | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 110-120    | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 120-130    | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 130-140    | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 140-150    | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 150-160    | 0.00   | 1502.25 | 100.00 | 100.00 |
| [OTHER] | 160-170    | 0.01   | 1502.26 | 100.00 | 100.00 |
| [OTHER] | 170-180    | 0.01   | 1502.27 | 100.00 | 100.00 |

## 4 – Spectral Flux Plots





## 5 – EUT Photos



## **6 – Luminous Intensity Distribution Test Plots (CIE Chromaticity)**

---

This page is blank and see next page.




## LUMINAIRE PHOTOMETRIC TEST REPORT


|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itgpp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |

| DATA OF LAMP     |                    | PHOTOMETRIC DATA Eff: 70.33 lm/W |        |                        |          |
|------------------|--------------------|----------------------------------|--------|------------------------|----------|
| MODEL            | 22TRMG4DIM/927/W/H | Imax(cd)                         | 7761   | S/MH(C0/180)           | 0.40     |
| NOMINAL POWER(W) | 22                 | LOR(%)                           | 100.0  | S/MH(C90/270)          | 0.37     |
| RATED VOLTAGE(V) | 120.0              | TOTAL FLUX(lm)                   | 1502.3 | $\eta$ UP,DN(C0-180)   | 0.0,46.0 |
| NOMINAL FLUX(lm) | 1502.27            | CIE CLASS                        | DIRECT | $\eta$ UP,DN(C180-360) | 0.0,54.0 |
| LAMPS INSIDE     | 1                  | $\eta$ up(%)                     | 0.0    | CIBSE SHR NOM          | 0.00     |
| TEST VOLTAGE(V)  | 120.0              | $\eta$ down(%)                   | 100.0  | CIBSE SHR MAX          | 1.00     |

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM(UNIT:lx)




C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2015-03-13

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.494m [K=1.0000]  
 Remarks:

ZONAL FLUX DIAGRAM  
AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

| γ   | C0                    | C45    | C90    | C135   | C180   | C225   | C270   | C315   | γ       | Φ zone  | Φ total | lum, lamp |
|-----|-----------------------|--------|--------|--------|--------|--------|--------|--------|---------|---------|---------|-----------|
| 10  | 3519                  | 3543   | 3870   | 4282   | 4752   | 4707   | 4303   | 3875   | 0- 10   | 549.3   | 549.3   | 36.6,36.6 |
| 20  | 750.7                 | 712.2  | 771.3  | 932.7  | 1154   | 1259   | 1164   | 958.3  | 10- 20  | 574.9   | 1124    | 74.8,74.8 |
| 30  | 167.3                 | 158.2  | 172.3  | 200.0  | 255.7  | 291.5  | 270.4  | 205.2  | 20- 30  | 221.2   | 1345    | 89.6,89.6 |
| 40  | 45.02                 | 46.70  | 53.33  | 55.76  | 58.39  | 59.58  | 56.76  | 47.88  | 30- 40  | 67.08   | 1412    | 94,94     |
| 50  | 32.22                 | 33.09  | 35.20  | 34.76  | 35.81  | 36.09  | 34.28  | 33.54  | 40- 50  | 31.79   | 1444    | 96.1,96.1 |
| 60  | 24.25                 | 24.75  | 25.84  | 26.99  | 28.11  | 28.22  | 26.54  | 25.71  | 50- 60  | 27.14   | 1471    | 97.9,97.9 |
| 70  | 13.39                 | 13.73  | 15.03  | 16.56  | 17.37  | 17.28  | 16.09  | 14.79  | 60- 70  | 20.94   | 1492    | 99.3,99.3 |
| 80  | 2.053                 | 2.191  | 2.691  | 3.164  | 3.693  | 3.649  | 3.269  | 2.693  | 70- 80  | 8.923   | 1501    | 99.9,99.9 |
| 90  | 0                     | 0      | 0.0000 | 0.0019 | 0.0740 | 0.0354 | 0      | 0      | 80- 90  | 0.9628  | 1502    | 100,100   |
| 100 | 0                     | 0      | 0      | 0      | 0      | 0      | 0      | 0      | 90-100  | 0.0006  | 1502    | 100,100   |
| 110 | 0                     | 0      | 0      | 0      | 0      | 0      | 0      | 0      | 100-110 | 0.0000  | 1502    | 100,100   |
| 120 | 0                     | 0      | 0      | 0      | 0      | 0      | 0      | 0      | 110-120 | 0.0000  | 1502    | 100,100   |
| 130 | 0                     | 0      | 0      | 0      | 0      | 0      | 0      | 0      | 120-130 | 0       | 1502    | 100,100   |
| 140 | 0                     | 0      | 0      | 0      | 0      | 0      | 0      | 0      | 130-140 | 0       | 1502    | 100,100   |
| 150 | 0                     | 0      | 0      | 0      | 0      | 0      | 0      | 0      | 140-150 | 0       | 1502    | 100,100   |
| 160 | 0.0132                | 0.0152 | 0.0139 | 0.0097 | 0.0091 | 0.0089 | 0.0103 | 0.0142 | 150-160 | 0.0010  | 1502    | 100,100   |
| 170 | 0.0826                | 0.0812 | 0.0763 | 0.0712 | 0.0748 | 0.0736 | 0.0752 | 0.0789 | 160-170 | 0.0104  | 1502    | 100,100   |
| 180 | 0                     | 0      | 0      | 0.0051 | 0      | 0.0012 | 0.0003 | 0      | 170-180 | 0.0080  | 1502    | 100,100   |
| DEG | LUMINOUS INTENSITY:cd |        |        |        |        |        |        |        |         | UNIT:lm |         |           |




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.6DEG  
Operators:David  
Test Date:2015-03-13

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity:67.1%  
Test Distance:2.494m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itggp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |

| pcc  | 80%                   |      |      | 70%                             |      |      | 50%  |      |      | 30%  |      |      | 10%  |      |      | 0   |
|------|-----------------------|------|------|---------------------------------|------|------|------|------|------|------|------|------|------|------|------|-----|
| pw   | 50%                   | 30%  | 10%  | 50%                             | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 0   |
| pfc  | 20%                   |      |      | 20%                             |      |      | 20%  |      |      | 20%  |      |      | 20%  |      |      | 0   |
| RCR  | RCR:Room Cavity Ratio |      |      | Coefficients of Utilization(CU) |      |      |      |      |      |      |      |      |      |      |      |     |
| 0.0  | 1.19                  | 1.19 | 1.19 | 1.16                            | 1.16 | 1.16 | 1.11 | 1.11 | 1.11 | 1.06 | 1.06 | 1.06 | 1.02 | 1.02 | 1.02 | .00 |
| 1.0  | 1.12                  | 1.10 | 1.08 | 1.10                            | 1.08 | 1.07 | 1.06 | 1.05 | 1.03 | 1.02 | 1.01 | 1.00 | .99  | .98  | .97  | .96 |
| 2.0  | 1.06                  | 1.03 | 1.00 | 1.05                            | 1.02 | .99  | 1.02 | .99  | .97  | .99  | .97  | .95  | .96  | .95  | .93  | .92 |
| 3.0  | 1.01                  | .98  | .94  | 1.00                            | .97  | .94  | .98  | .95  | .92  | .95  | .93  | .91  | .93  | .91  | .89  | .88 |
| 4.0  | .97                   | .93  | .90  | .96                             | .92  | .89  | .94  | .91  | .88  | .92  | .89  | .87  | .90  | .88  | .86  | .85 |
| 5.0  | .93                   | .89  | .86  | .92                             | .88  | .85  | .91  | .87  | .84  | .89  | .86  | .84  | .88  | .85  | .83  | .82 |
| 6.0  | .90                   | .85  | .82  | .89                             | .85  | .82  | .88  | .84  | .81  | .87  | .83  | .81  | .85  | .83  | .80  | .79 |
| 7.0  | .87                   | .82  | .79  | .86                             | .82  | .79  | .85  | .81  | .79  | .84  | .81  | .78  | .83  | .80  | .78  | .77 |
| 8.0  | .84                   | .80  | .77  | .84                             | .79  | .77  | .83  | .79  | .76  | .82  | .78  | .76  | .81  | .78  | .76  | .75 |
| 9.0  | .82                   | .77  | .74  | .81                             | .77  | .74  | .80  | .77  | .74  | .80  | .76  | .74  | .79  | .76  | .74  | .73 |
| 10.0 | .79                   | .75  | .72  | .79                             | .75  | .72  | .78  | .75  | .72  | .78  | .74  | .72  | .77  | .74  | .72  | .71 |



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2015-03-13

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.494m [K=1.0000]  
 Remarks:

## WEC AND CCEC

|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itgpp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |

| pcc  | 80%                   |      |      | 70%  |      |      | 50%                             |      |      | 30%  |      |      | 10%  |      |      | 0 |
|------|-----------------------|------|------|------|------|------|---------------------------------|------|------|------|------|------|------|------|------|---|
| pw   | 50%                   | 30%  | 10%  | 50%  | 30%  | 10%  | 50%                             | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 0 |
| pfc  | 20%                   |      |      | 20%  |      |      | 20%                             |      |      | 20%  |      |      | 20%  |      |      | 0 |
| RCR  | RCR:Room Cavity Ratio |      |      |      |      |      | Wall Exitance Coefficients(WEC) |      |      |      |      |      |      |      |      |   |
| 0.0  |                       |      |      |      |      |      |                                 |      |      |      |      |      |      |      |      |   |
| 1.0  | .148                  | .084 | .027 | .142 | .081 | .026 | .129                            | .074 | .024 | .118 | .068 | .022 | .107 | .062 | .020 |   |
| 2.0  | .138                  | .076 | .023 | .133 | .073 | .023 | .122                            | .068 | .021 | .113 | .063 | .020 | .104 | .059 | .019 |   |
| 3.0  | .129                  | .068 | .020 | .124 | .066 | .020 | .115                            | .063 | .019 | .107 | .059 | .018 | .100 | .055 | .017 |   |
| 4.0  | .120                  | .062 | .018 | .116 | .061 | .018 | .109                            | .058 | .017 | .102 | .055 | .017 | .096 | .052 | .016 |   |
| 5.0  | .113                  | .057 | .017 | .109 | .056 | .016 | .103                            | .054 | .016 | .097 | .051 | .015 | .092 | .049 | .015 |   |
| 6.0  | .106                  | .053 | .015 | .103 | .052 | .015 | .098                            | .050 | .015 | .093 | .048 | .014 | .088 | .046 | .014 |   |
| 7.0  | .100                  | .050 | .014 | .098 | .049 | .014 | .093                            | .047 | .014 | .089 | .045 | .013 | .085 | .044 | .013 |   |
| 8.0  | .095                  | .047 | .013 | .093 | .046 | .013 | .089                            | .044 | .013 | .085 | .043 | .012 | .081 | .042 | .012 |   |
| 9.0  | .091                  | .044 | .012 | .089 | .043 | .012 | .085                            | .042 | .012 | .082 | .041 | .012 | .078 | .040 | .012 |   |
| 10.0 | .086                  | .041 | .012 | .085 | .041 | .011 | .082                            | .040 | .011 | .078 | .039 | .011 | .076 | .038 | .011 |   |

| pcc  | 80%                   |      |      | 70%  |      |      | 50%  |      |      | 30%  |      |      | 10%  |      |      | 0 |
|------|-----------------------|------|------|------|------|------|--|------|------|------|------|------|------|------|------|---|
| pw   | 50%                   | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 50%  | 30%  | 10%  | 0 |
| pfc  | 20%                   |      |      | 20%  |      |      | 20%  |      |      | 20%  |      |      | 20%  |      |      | 0 |
| RCR  | RCR:Room Cavity Ratio |      |      |      |      |      | Ceiling Cavity Exitance Coefficients(CCEC) |      |      |      |      |      |      |      |      |   |
| 0.0  | .190                  | .190 | .190 | .163 | .163 | .163 | .111                                       | .111 | .111 | .064 | .064 | .064 | .020 | .020 | .020 |   |
| 1.0  | .169                  | .158 | .147 | .145 | .135 | .127 | .099                                       | .093 | .088 | .057 | .054 | .051 | .018 | .017 | .016 |   |
| 2.0  | .152                  | .133 | .117 | .130 | .114 | .101 | .089                                       | .079 | .070 | .051 | .046 | .041 | .016 | .015 | .013 |   |
| 3.0  | .137                  | .113 | .094 | .118 | .098 | .082 | .081                                       | .068 | .057 | .047 | .040 | .034 | .015 | .013 | .011 |   |
| 4.0  | .125                  | .098 | .078 | .107 | .085 | .067 | .074                                       | .059 | .047 | .043 | .035 | .028 | .014 | .011 | .009 |   |
| 5.0  | .115                  | .086 | .065 | .098 | .074 | .056 | .068                                       | .052 | .040 | .039 | .030 | .024 | .013 | .010 | .008 |   |
| 6.0  | .106                  | .076 | .055 | .091 | .066 | .048 | .063                                       | .046 | .034 | .036 | .027 | .020 | .012 | .009 | .007 |   |
| 7.0  | .098                  | .068 | .047 | .084 | .059 | .041 | .058                                       | .041 | .029 | .034 | .024 | .017 | .011 | .008 | .006 |   |
| 8.0  | .092                  | .061 | .040 | .079 | .053 | .035 | .055                                       | .037 | .025 | .032 | .022 | .015 | .010 | .007 | .005 |   |
| 9.0  | .086                  | .056 | .035 | .074 | .048 | .031 | .051                                       | .034 | .022 | .030 | .020 | .013 | .010 | .007 | .004 |   |
| 10.0 | .081                  | .051 | .031 | .070 | .044 | .027 | .048                                       | .031 | .019 | .028 | .018 | .011 | .009 | .006 | .004 |   |

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2015-03-13

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.494m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

|   |               |                  |      |      |                         |               |                |                   |      |      |      |      |
|---|---------------|------------------|------|------|-------------------------|---------------|----------------|-------------------|------|------|------|------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |               |                  |      |      |                         |               |                |                   |      |      |      |      |
| NAME:   |               |                  |      |      | TYPE:44VTOI6FK01;491Y1J |               |                | WEIGHT:           |      |      |      |      |
| SPEC.:  |               |                  |      |      | DIM.:                   |               |                | SERIAL No.:       |      |      |      |      |
| MFR.: Itggp"Etgcvkxg  |               |                  |      |      | SUR.:                   |               |                | PROTECTION ANGLE: |      |      |      |      |
| ceiling/cavity  | 0.7           | 0.7              | 0.5  | 0.5  | 0.3                     | 0.7           | 0.7            | 0.5               | 0.5  | 0.3  |      |      |
| walls   | 0.5           | 0.3              | 0.5  | 0.3  | 0.3                     | 0.5           | 0.3            | 0.5               | 0.3  | 0.3  |      |      |
| working plane   | 0.2           | 0.2              | 0.2  | 0.2  | 0.2                     | 0.2           | 0.2            | 0.2               | 0.2  | 0.2  |      |      |
| Room dimensions   |               | Viewed crosswise |      |      |                         |               | Viewed endwise |                   |      |      |      |      |
| x = 2H y = 2H   | 2H            | 16.8             | 17.5 | 17.0 | 17.6                    | 17.8          | 17.1           | 17.8              | 17.3 | 18.0 | 18.1 |      |
|   | 3H            | 18.0             | 18.7 | 18.3 | 18.9                    | 19.0          | 18.4           | 19.1              | 18.7 | 19.3 | 19.5 |      |
|   | 4H            | 18.3             | 18.9 | 18.5 | 19.1                    | 19.3          | 18.7           | 19.4              | 19.0 | 19.6 | 19.8 |      |
|   | 6H            | 18.3             | 18.9 | 18.6 | 19.1                    | 19.4          | 18.8           | 19.4              | 19.1 | 19.6 | 19.9 |      |
|   | 8H            | 18.3             | 18.8 | 18.6 | 19.1                    | 19.3          | 18.8           | 19.3              | 19.1 | 19.6 | 19.8 |      |
|   | 12H           | 18.2             | 18.8 | 18.5 | 19.0                    | 19.3          | 18.7           | 19.3              | 19.0 | 19.5 | 19.8 |      |
|   | 4H            | 2H               | 17.4 | 18.0 | 17.6                    | 18.2          | 18.4           | 17.7              | 18.3 | 18.0 | 18.5 | 18.7 |
|   | 3H            | 18.7             | 19.3 | 19.0 | 19.5                    | 19.8          | 19.1           | 19.6              | 19.4 | 19.9 | 20.2 |      |
|   | 4H            | 19.0             | 19.5 | 19.4 | 19.8                    | 20.1          | 19.4           | 19.9              | 19.8 | 20.2 | 20.5 |      |
|   | 6H            | 19.1             | 19.5 | 19.4 | 19.8                    | 20.2          | 19.5           | 19.9              | 19.9 | 20.3 | 20.6 |      |
|   | 8H            | 19.0             | 19.4 | 19.4 | 19.8                    | 20.2          | 19.5           | 19.9              | 19.9 | 20.2 | 20.6 |      |
|   | 12H           | 19.0             | 19.4 | 19.4 | 19.7                    | 20.1          | 19.4           | 19.8              | 19.8 | 20.2 | 20.6 |      |
| 8H  | 4H            | 19.1             | 19.5 | 19.5 | 19.8                    | 20.2          | 19.5           | 19.9              | 19.8 | 20.2 | 20.6 |      |
| 6H  | 19.1          | 19.5             | 19.6 | 19.9 | 20.3                    | 19.5          | 19.9           | 20.0              | 20.3 | 20.7 |      |      |
| 8H  | 19.1          | 19.4             | 19.5 | 19.8 | 20.3                    | 19.5          | 19.8           | 20.0              | 20.2 | 20.7 |      |      |
| 12H   | 19.0          | 19.3             | 19.5 | 19.8 | 20.2                    | 19.5          | 19.7           | 19.9              | 20.2 | 20.6 |      |      |
| 12H   | 4H            | 19.0             | 19.4 | 19.4 | 19.8                    | 20.2          | 19.4           | 19.8              | 19.8 | 20.2 | 20.5 |      |
| 6H  | 19.1          | 19.4             | 19.5 | 19.8 | 20.2                    | 19.5          | 19.8           | 19.9              | 20.2 | 20.7 |      |      |
| 8H  | 19.0          | 19.3             | 19.5 | 19.8 | 20.2                    | 19.5          | 19.7           | 19.9              | 20.2 | 20.6 |      |      |
| Variations with the observer position at spacings:                |               |                  |      |      |                         |               |                |                   |      |      |      |      |
| S = 1.0H  | + 0.2 / - 0.4 |                  |      |      |                         | + 0.3 / - 0.4 |                |                   |      |      |      |      |
| 1.5H  | + 0.1 / - 0.3 |                  |      |      |                         | + 0.3 / - 0.3 |                |                   |      |      |      |      |
| 2.0H  | + 0.2 / - 0.4 |                  |      |      |                         | + 0.3 / - 0.5 |                |                   |      |      |      |      |

CIE Pub.117 Corrected 1502 lm Total Lamp Luminous Flux.(8log(F/F0) = 1.4)

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2015-03-13

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.494m [K=1.0000]  
 Remarks:

## UTILIZATION FACTORS TABLE

|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itggp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |

| REFLECTANCE                      |   |     |           |     |     |     |     |               |     |        |
|----------------------------------|---|-----|-----------|-----|-----|-----|-----|---------------|-----|--------|
| Ceiling                          | 0.8   | 0.8 | 0.8       | 0.7 | 0.7 | 0.7 | 0.5 | 0.5           | 0.5 | 0      |
| Walls                            | 0.7   | 0.5 | 0.3       | 0.7 | 0.5 | 0.3 | 0.7 | 0.5           | 0.3 | 0      |
| Working plane                    | 0.2   | 0.2 | 0.2       | 0.2 | 0.2 | 0.2 | 0.2 | 0.2           | 0.2 | 0      |
| ROOM INDEX                       | UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$ |     |           |     |     |     |     |               |     |        |
| $k = 0.60$                       | 88  | 82  | 78        | 87  | 81  | 78  | 87  | 81            | 78  | 74     |
| 0.80                             | 95  | 89  | 86        | 94  | 89  | 86  | 93  | 88            | 85  | 82     |
| 1.00                             | 99  | 94  | 90        | 98  | 93  | 90  | 97  | 93            | 89  | 85     |
| 1.25                             | 103   | 98  | 95        | 102 | 97  | 94  | 100 | 96            | 93  | 89     |
| 1.50                             | 106   | 101 | 98        | 105 | 100 | 97  | 102 | 99            | 96  | 92     |
| 2.00                             | 108   | 104 | 101       | 107 | 103 | 100 | 104 | 101           | 99  | 94     |
| 2.50                             | 110   | 106 | 103       | 109 | 105 | 102 | 105 | 103           | 101 | 95     |
| 3.00                             | 112   | 108 | 106       | 110 | 107 | 104 | 107 | 104           | 102 | 96     |
| 4.00                             | 114   | 111 | 109       | 112 | 109 | 107 | 108 | 106           | 105 | 98     |
| 5.00                             | 115   | 113 | 111       | 113 | 111 | 109 | 109 | 108           | 106 | 99     |
| ROOM INDEX                       | UF(total)   |     |           |     |     |     |     |               |     | Direct |
| According to DIN EN 13032-2 2004 |   |     | Suspended |     |     |     |     | SHRNOM = 1.25 |     |        |

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2015-03-13

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.494m [K=1.0000]  
 Remarks:



## ISOCANDELA DIAGRAM

|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itggp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |

Conical surface Flux(90deg):

1429.3 lm

%lum = 95.1%


%lamp = 95.1%

Conical surface Flux(20deg):

1471.4 lm

%lum = 97.9%

%lamp = 97.9%




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.6DEG  
Operators:David  
Test Date:2015-03-13

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity:67.1%  
Test Distance:2.494m [K=1.0000]  
Remarks:

## AAI Figure

|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itggp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.6DEG  
Operators:David  
Test Date:2015-03-13

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity:67.1%  
Test Distance:2.494m [K=1.0000]  
Remarks:

## ISOLUX DIAGRAM


|   |                         |                   |
|---|-------------------------|-------------------|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |                         |                   |
| NAME:   | TYPE:44VTOI6FK01;491Y1J | WEIGHT:           |
| SPEC.:  | DIM.:                   | SERIAL No.:       |
| MFR.: Itggp"Etgcvkxg  | SUR.:                   | PROTECTION ANGLE: |



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.6DEG  
 Operators: David  
 Test Date: 2015-03-13

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity: 67.1%  
 Test Distance: 2.494m [K=1.0000]  
 Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.6DEG  
Operators: David  
Test Date: 2015-03-13

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity: 67.1%  
Test Distance: 2.494m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

|   |  |  |  |  |  |  |  |  |                         |  |  |  |  |  |                   |  |  |
|---|--|--|--|--|--|--|--|--|-------------------------|--|--|--|--|--|-------------------|--|--|
| Test:U:120.0V I:0.1820A P:21.36W PF:0.9768 Lamp Flux:1502.27x1 lm |  |  |  |  |  |  |  |  |                         |  |  |  |  |  |                   |  |  |
| NAME:   |  |  |  |  |  |  |  |  | TYPE:44VTOI6FK01;491Y1J |  |  |  |  |  | WEIGHT:           |  |  |
| SPEC.:  |  |  |  |  |  |  |  |  | DIM.:                   |  |  |  |  |  | SERIAL No.:       |  |  |
| MFR.: Itggp"Etgcvkxg  |  |  |  |  |  |  |  |  | SUR.:                   |  |  |  |  |  | PROTECTION ANGLE: |  |  |


Table--1

UNIT: cd

| C (DEG)<br>γ (DEG) | 0    | 23   | 45   | 68   | 90   | 113  | 135  | 158  | 180  | 203  | 225  | 248  | 270  | 293  | 315  | 338  |  |  |  |
|--------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|--|--|--|
| 0                  | 7729 | 7718 | 7722 | 7719 | 7724 | 7724 | 7725 | 7726 | 7729 | 7718 | 7722 | 7719 | 7724 | 7724 | 7725 | 7726 |  |  |  |
| 5                  | 6248 | 6239 | 6278 | 6368 | 6502 | 6666 | 6811 | 6928 | 7076 | 7109 | 7065 | 6950 | 6813 | 6658 | 6511 | 6404 |  |  |  |
| 10                 | 3519 | 3494 | 3543 | 3693 | 3870 | 4071 | 4282 | 4464 | 4752 | 4800 | 4707 | 4526 | 4303 | 4087 | 3875 | 3707 |  |  |  |
| 15                 | 1618 | 1586 | 1585 | 1654 | 1780 | 1921 | 2096 | 2229 | 2409 | 2449 | 2440 | 2351 | 2198 | 2058 | 1904 | 1766 |  |  |  |
| 20                 | 751  | 733  | 712  | 714  | 771  | 842  | 933  | 1036 | 1154 | 1222 | 1259 | 1222 | 1164 | 1067 | 958  | 860  |  |  |  |
| 25                 | 359  | 352  | 340  | 333  | 352  | 376  | 411  | 461  | 529  | 579  | 606  | 602  | 583  | 519  | 451  | 393  |  |  |  |
| 30                 | 167  | 161  | 158  | 166  | 172  | 183  | 200  | 220  | 256  | 272  | 291  | 298  | 270  | 246  | 205  | 179  |  |  |  |
| 35                 | 71.9 | 70.1 | 72.9 | 81.5 | 84.9 | 88.9 | 95.3 | 103  | 118  | 120  | 130  | 138  | 117  | 101  | 85.1 | 76.1 |  |  |  |
| 40                 | 45.0 | 44.6 | 46.7 | 52.0 | 53.3 | 54.6 | 55.8 | 56.8 | 58.4 | 58.3 | 59.6 | 59.6 | 56.8 | 50.7 | 47.9 | 46.2 |  |  |  |
| 45                 | 36.9 | 37.6 | 38.5 | 40.5 | 41.7 | 41.1 | 40.7 | 41.1 | 42.0 | 42.2 | 42.1 | 42.3 | 41.7 | 39.8 | 38.8 | 38.0 |  |  |  |
| 50                 | 32.2 | 32.6 | 33.1 | 34.5 | 35.2 | 34.8 | 34.8 | 35.2 | 35.8 | 35.9 | 36.1 | 35.2 | 34.3 | 33.6 | 33.5 | 32.4 |  |  |  |
| 55                 | 28.6 | 28.8 | 29.2 | 30.0 | 30.4 | 30.7 | 31.0 | 31.4 | 31.9 | 32.0 | 32.0 | 31.1 | 30.4 | 29.8 | 29.8 | 28.9 |  |  |  |
| 60                 | 24.2 | 24.5 | 24.8 | 25.5 | 25.8 | 26.4 | 27.0 | 27.8 | 28.1 | 28.2 | 28.2 | 27.2 | 26.5 | 25.8 | 25.7 | 24.9 |  |  |  |
| 65                 | 19.3 | 19.3 | 19.7 | 20.1 | 20.6 | 21.2 | 21.9 | 22.4 | 22.7 | 23.1 | 23.1 | 22.4 | 21.9 | 21.1 | 20.7 | 20.1 |  |  |  |
| 70                 | 13.4 | 13.4 | 13.7 | 14.3 | 15.0 | 15.8 | 16.6 | 16.8 | 17.4 | 17.4 | 17.3 | 16.8 | 16.1 | 15.2 | 14.8 | 14.1 |  |  |  |
| 75                 | 6.62 | 6.59 | 6.78 | 7.09 | 7.46 | 7.90 | 8.36 | 8.83 | 9.43 | 9.49 | 9.21 | 8.69 | 8.22 | 7.90 | 7.52 | 7.14 |  |  |  |
| 80                 | 2.05 | 2.06 | 2.19 | 2.43 | 2.69 | 2.96 | 3.16 | 3.33 | 3.69 | 3.71 | 3.65 | 3.50 | 3.27 | 2.97 | 2.69 | 2.42 |  |  |  |
| 85                 | 0.46 | 0.47 | 0.49 | 0.53 | 0.60 | 0.66 | 0.71 | 0.75 | 0.81 | 0.80 | 0.78 | 0.73 | 0.67 | 0.62 | 0.56 | 0.52 |  |  |  |
| 90                 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.07 | 0.07 | 0.04 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 95                 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 100                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 105                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 110                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 115                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 120                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 125                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 130                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 135                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 140                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 145                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 150                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 155                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |
| 160                | 0.01 | 0.01 | 0.02 | 0.02 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.02 |  |  |  |
| 165                | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.04 | 0.03 | 0.03 | 0.03 | 0.03 | 0.03 | 0.03 | 0.04 | 0.04 | 0.04 | 0.04 |  |  |  |
| 170                | 0.08 | 0.08 | 0.08 | 0.08 | 0.08 | 0.07 | 0.07 | 0.07 | 0.07 | 0.07 | 0.07 | 0.07 | 0.08 | 0.08 | 0.08 | 0.08 |  |  |  |
| 175                | 0.09 | 0.09 | 0.09 | 0.08 | 0.08 | 0.09 | 0.09 | 0.09 | 0.10 | 0.10 | 0.10 | 0.10 | 0.09 | 0.09 | 0.09 | 0.09 |  |  |  |
| 180                | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |  |  |  |


C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.6DEG  
 Operators: David  
 Test Date: 2015-03-13

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity: 67.1%  
 Test Distance: 2.494m [K=1.0000]  
 Remarks:



1000 lm

$\kappa = 1$



F = 5000 lm  
 K = 0.7  
 Hcc = 0.0 m  
 Hfc = 0.0 m  
 Eave = 100 lx

|       | Pcc | Pw | Pfc |
|-------|-----|----|-----|
| ————— | 70  | 50 | 30  |
| ————— | 50  | 30 | 20  |

