

# IESNA LM-79: 2008

## Measurement and Test Report

for

### Green Creative Ltd.

Room 1206-7, New Victory House, 93-103 Wing Lok Street, Central, HONG KONG

May 21, 2015

<b>Product Name:</b>	LED TRACK LAMP
<b>Model No:</b>	8TRSG4DIM/827NF30/B/H; 8TRSG4DIM/827NF30/B/J; 8TRSG4DIM/827NF30/B/L; 8TRSG4DIM/827NF30/W/H; 8TRSG4DIM/827NF30/W/J; 8TRSG4DIM/827NF30/W/L
<b>Test Engineer:</b>	David Zhang 
<b>Report No.:</b>	BTR66.181.14.0057.03
<b>Sample Received Date:</b>	Dec 10, 2014
<b>Test Performed Date:</b>	Dec 10, 2014 to Dec 16, 2014
<b>Reviewed By:</b>	Steven Hsu 
<b>Prepared By:</b>	<b>BEST Test Service Shenzhen Co., Ltd.</b> 1st Floor, 1st Building, Weitai Industrial Park, Yingrenshi, Shiyuan, Baoan, Shenzhen, China TEL: +86-755-28236006 FAX: +86-755-23467087-811 Email: <a href="mailto:certification@bestcert.cn">certification@bestcert.cn</a>



**Note:** This report is not valid as a BEST Test Report unless signed by an approved BEST Test Service Shenzhen Co., Ltd. This report shall not be reproduced except in full without the written approval of the testing laboratory. The test report only allows to be revised within the retention period unless further standard or the requirement was noticed. This report is for the exclusive use of BEST's Client and is provided pursuant to the agreement between BEST and its Client. BEST's responsibility and Liability are limited to the terms and conditions of the agreement. BEST assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the BEST name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by BEST. The observations and test results in this report are relevant only to the sample tested. This report by itself does not cover that the material, product, of service is or has ever been under a BEST certification program. National Voluntary Laboratory Accreditation Program (NVLAP) has accredited this laboratory under ISO17025: 2005 for specific laboratory activities as listed in the NVLAP directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation. This report must not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the U.S. Government.

**TABLE OF CONTENTS**

<b>1 - GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	3
1.2 OBJECTIVE .....	3
1.3 TEST FACILITY DESCRIPTION.....	4
1.4 TEST EQUIPMENT LIST .....	4
<b>2 - TEST METHOD.....</b>	<b>5</b>
2.1 PHOTOMETRIC AND ELECTRICAL MEASUREMENT (INTEGRATED SPHERE METHOD) .....	5
2.2 PHOTOMETRIC AND ELECTRICAL MEASUREMENT (GONIOPHOTOMETER METHOD) .....	5
2.3 DEVIATION FROM STANDARD OPERATING PROCEDURE .....	5
<b>3 - SUMMARY OF TEST RESULT .....</b>	<b>6</b>
<b>4 - SPECTRAL FLUX PLOTS .....</b>	<b>8</b>
<b>5 - EUT PHOTOS.....</b>	<b>9</b>
<b>6 - LUMINOUS INTENSITY DISTRIBUTION TEST PLOTS (CIE CHROMATICITY).....</b>	<b>10</b>



## 1 - GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

Applicant	: Green Creative Ltd.
Product Name	: LED TRACK LAMP
Model No	: 8TRSG4DIM/827NF30/B/H; 8TRSG4DIM/827NF30/B/J; 8TRSG4DIM/827NF30/B/L; 8TRSG4DIM/827NF30/W/H; 8TRSG4DIM/827NF30/W/J; 8TRSG4DIM/827NF30/W/L
Brand	: GREEN CREATIVE
Nominal Operation Voltage	: AC 120V/60Hz
Nominal Power	: 8.5 W
Nominal CCT	: 2700K
Nominal CRI	: 80
Nominal Lumen Output	: 550 Lumens
Nominal Life Time	: 40000 Hours
Number of hours operated prior to measurement for new sample	: 0 Hours
Stabilization Time	: 1.0 hours
Total operating time for measurement include stabilization time	: 2.5 hours
Date of Receiving Sample	: Dec 10, 2014
Measurement quantities measured	: 1 pcs
Orientation During Testing	: Base up
Test Requested	: Electrical and Photometric Test Luminous Intensity Distribution Test

Note: 8TRSG4DIM/827NF30/B/J; 8TRSG4DIM/827NF30/B/L; 8TRSG4DIM/827NF30/W/H; 8TRSG4DIM/827NF30/W/J; 8TRSG4DIM/827NF30/W/L and 8TRSG4DIM/827NF30/B/H are only lamp base and color different, here we choose 8TRSG4DIM/827NF30/B/H to be tested and others to share the test data.

### 1.2 Objective

The following test report is prepared on behalf of Green Creative Ltd. in accordance with IESNA LM-79-08, used the following American National Standards or Illumination Engineering Society of North America test guides:

ANSI C78.377-2008: Specifications for the Chromaticity of Solid State Lighting Products;

ANSI C79.1-2002: American National Standard for Electric Lamps – Nomenclature for Glass Bulbs Intended for Use with Electric Lamps;

ANSI C78.20-2003: American National Standard for Electric Lamps – A, G, PS, and Similar Shapes with E26 Medium Screw Bases;

ANSI C78.21-2011: American National Standard for Electric Lamps – PAR and R Shapes;

ANSI C78.24-2001: American National Standard for Electric Lamps – Two-inch (51 mm);

Integral-reflector Lamps with Front Covers and GU5.3 or GX 5.3 Bases;

ANSI/IEC C81.61-2003: American National Standard for Electric Lamp Bases;

ANSI/IEEE C62.41-1991 (01-May-1991): Surge Voltages in Low-Voltage AC Power Circuits, Recommended Practice for;

CIE Publication No. 13.3-1995: Method of Measuring and Specifying Color Rendering of Light Sources;

CIE Publication No. 18.2-1983: The Basis of Physical Photometry;

IESNA LM-16-1993: Practical Guide to Colorimetry of Light Sources;

IESNA LM-28-89-1989: Guide for the Selection, Care, and Use of Electrical Instruments in the Photometric Laboratory;

IESNA LM-79-08 Electrical and Photometric Measurement of Solid State Lighting Products

UL 1993-1999: Standard for Self-Ballasted Lamps and Lamp Adapters;

UL 8750-2009: Light Emitting Diode (LED) Equipment for Use in Lighting Products.

### 1.3 Test Facility Description

The Energy Efficiency Lab used by BEST to collect energy efficiency measurement data is located in 1st Floor, 1st Building, Weitai Industrial Park, Yingrenshi, Shiyao, Baoan, Shenzhen, China. BEST Test Service Shenzhen Co., Ltd is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200770-0). BEST Test Service Shenzhen Co., Ltd is also an ELI accredited lab for lighting products (ELI Certificate No. ELI-L04-2010) and UL accredited lab for lighting products

### 1.4 Test Equipment List

Apparatus List	Device	Cal. Date	Cal Due Date
1	Integral Sphere+ Spectrophotometer System	Mar 10, 2015	Mar 09, 2016
2	Digital Power Meter	Oct 18, 2014	Oct 17, 2015
3	Goniophotometer+ Spectrophotometer System	Nov 20, 2014	Nov 19, 2015
4	Standard Light Source	Sep 17, 2014	Sep 16, 2015
5	Standard Light Source	Sep 17, 2014	Sep 16, 2015
6	Digital Storage Oscilloscope	Oct 18, 2014	Oct 17, 2015
7	Ultra Compact Simulator	Oct 20, 2014	Oct 19, 2015
8	Temperature Chamber	Oct 20, 2014	Oct 19, 2015
9	Digital Caliper	Nov 20, 2014	Nov 19, 2015
10	Digital CC&CV DC Power Supply(30V 5A)	N/A	N/A
11	5 1/2 Digital Multimeter	Oct 18, 2014	Oct 17, 2015
12	Digital CC&CV DC Power Supply(120V 10A)	N/A	N/A
13	6 1/2 Digital Multimeter	Oct 18, 2014	Oct 17, 2015
14	Digital Multimeter	Oct 18, 2014	Oct 17, 2015
15	Temperature Recorder+Thermocouple	Nov 20, 2014	Nov 19, 2015
16	Timer Controller	Nov 20, 2014	Nov 19, 2015

**Statement of Traceability:** BEST Test Service Shenzhen Co., Ltd. certifies that all calibration has been performed using suitable standards traceable to the NIM China.

## 2 - Test Method

### 2.1 Photometric and Electrical Measurement (Integrated Sphere Method)

Total light output (luminous flux) for the  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$  ambient temperature conditions is measured using a 1.6m  $\Phi$  geometry integrating sphere. Temperature is measured at a position inside the sphere. Spectral radiant flux measurements are made using Lab sphere to the detector port of the integrating sphere. Each lamp is operated at rated voltage in its designated orientation. Each lamp should be stable before measurements are made. The determining method of stable is as follows:

Step 1 Take 3 measurements of the lamp light output at 15 minute interval (total time=30minutes.) This time period is in addition to the recommended pre-burning time.

Step 2 Calculate the percent difference between the maximum measured value and the minimum measured value for the three consecutive measurements.

Step 3 If the value calculated in Step 2 does not exceed 0.5 percent, the lamp is considered stable. Luminous flux, chromaticity coordinates, correlated color temperature and color rendering index for each lamp are calculated from the spectral radiant flux measurements taken at 2 nm intervals over the range 350 to 1050 nm. The calibration of the sphere photometer-spectrometer system is traceable to the NIST USA. Lamp efficacy (lumens per watts) for each lamp model is computed based on the revised luminous flux result. Electrical measurements including voltage, current, power and power factor are measured using the digital power Meter.

The total uncertainty of the light output measurements is estimated, at the 95% confidence level, not to exceed  $\pm 1.12\%$  over the wavelength range 350-1050 nm.

### 2.2 Photometric and Electrical Measurement (Goniophotometer Method)

A Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample; the photometric distance is 24m. Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to be stable before measurement was made. Electrical measurements including voltage, current, power and power factor were measured using the Power Analyzer

Before each measurement, the method below should be used to determine the lamp is stable or not.

Step 1 Take 3 measurements of the lamp intensity at 15 minute interval (total time=30minutes.) This time period is in addition to the recommended pre-burning time.

Step 2 Calculate the percent difference between the maximum measured value and the minimum measured value for the three consecutive measurements.

Step 3 If the value calculated in Step 2 does not exceed 0.5 percent, the lamp is considered stable.

Some graphics were created with Photometric Plus software.

### 2.3 Deviation from standard operating procedure

None.

### 3 – Summary of Test Result

	Item	Test Result		Accreditation
Required Fields	Lumen Output (Lumens)	755.62		NVLAP/EPA
	Luminous Efficacy (lm/w)	91.08		NVLAP/EPA
	Correlated Color Temperature (CCT)	2766		NVLAP/EPA
	Color Rendering Index– CRI	81.4		NVLAP/EPA
	Input Power (W)	8.30		NVLAP/EPA
Optional Fields	Power Type	<input checked="" type="checkbox"/> AC	<input type="checkbox"/> DC	/
	Input Voltage (V)	120.0		NVLAP/EPA
	Input Current (A)	0.0752		NVLAP/EPA
	Power Factor	0.9175		NVLAP/EPA
	x(CIE 1931)	0.4524		NVLAP/EPA
	y(CIE 1931)	0.4054		NVLAP/EPA
	u' (CIE 1976)	0.2600		NVLAP/EPA
	v' (CIE 1976)	0.5242		NVLAP/EPA
	Duv(CIE 1976)	0.0013		NVLAP/EPA
	Beam Angle: (Degree)	25.9		NVLAP/EPA
	Center beam candlepower: (cd)	2389		NVLAP/EPA
	Zonal lumen density (0-60°):	97.2%		NVLAP/EPA
	Zonal lumen density (60-90°):	2.8%		NVLAP/EPA
	Zonal lumen density (90-120°):	0.0%		NVLAP/EPA
	Zonal lumen density (120-180°):	0.0%		NVLAP/EPA


	CRI (R1)	80	NVLAP/EPA
	CRI (R2)	90	NVLAP/EPA
	CRI (R3)	96	NVLAP/EPA
	CRI (R4)	79	NVLAP/EPA
	CRI (R5)	79	NVLAP/EPA
	CRI (R6)	88	NVLAP/EPA
	CRI (R7)	82	NVLAP/EPA
	CRI (R8)	57	NVLAP/EPA
	CRI (R9)	6	NVLAP/EPA
	CRI (R10)	78	NVLAP/EPA
	CRI (R11)	77	NVLAP/EPA
	CRI (R12)	71	NVLAP/EPA
	CRI (R13)	82	NVLAP/EPA
	CRI (R14)	99	NVLAP/EPA

**Lumen summary:**

[OTHER]	Gamma(deg)	Fz (lm)	Ft (lm)	%Lum	%Lamp
[OTHER]	0- 10	183.75	183.75	24.32	24.32
[OTHER]	10- 20	266.56	450.31	59.59	59.59
[OTHER]	20- 30	148.66	598.97	79.27	79.27
[OTHER]	30- 40	73.73	672.70	89.03	89.03
[OTHER]	40- 50	37.98	710.68	94.05	94.05
[OTHER]	50- 60	23.79	734.47	97.20	97.20
[OTHER]	60- 70	14.93	749.39	99.18	99.18
[OTHER]	70- 80	5.61	755.01	99.92	99.92
[OTHER]	80- 90	0.56	755.56	99.99	99.99
[OTHER]	90-100	0.00	755.57	99.99	99.99
[OTHER]	100-110	0.00	755.57	99.99	99.99
[OTHER]	110-120	0.00	755.57	99.99	99.99
[OTHER]	120-130	0.00	755.57	99.99	99.99
[OTHER]	130-140	0.00	755.57	99.99	99.99
[OTHER]	140-150	0.00	755.57	99.99	99.99
[OTHER]	150-160	0.02	755.59	99.99	99.99
[OTHER]	160-170	0.03	755.61	100.00	100.00
[OTHER]	170-180	0.01	755.63	100.00	100.00



## 4 – Spectral Flux Plots





## 5 – EUT Photos

---



## **6 – Luminous Intensity Distribution Test Plots (CIE Chromaticity)**

---

This page is blank and see next page.




## LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: GC	SUR.:	PROTECTION ANGLE:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 91.08 lm/W			
MODEL:TL03-550-27K-24D DIM/W		I <sub>max</sub> (cd)	2389	S/MH (C0/180)	0.49
NOMINAL POWER (W)	8.5	LOR (%)	100.0	S/MH (C90/270)	0.40
RATED VOLTAGE (V)	120.0	TOTAL FLUX (lm)	755.63	η UP, DN (C0-180)	0.0, 52.4
NOMINAL FLUX (lm)	755.625	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 47.5
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	120.0	η down (%)	100.0	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



PLANAR ISOLUX DIAGRAM (UNIT: lx)




C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.6DEG  
 Operators: David  
 Test Date: 2014-12-22

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity: 67.1%  
 Test Distance: 2.508m [K=1.0000]  
 Remarks:

ZONAL FLUX DIAGRAM  
AND LUMINANCE LIMITATION CURVES

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	ℓlum,lamp
10	1337	1496	1689	1777	1740	1564	1409	1344	0- 10	183.7	183.7	24.3,24.3
20	417.0	510.2	647.4	706.4	685.5	571.7	461.6	402.1	10- 20	266.6	450.3	59.6,59.6
30	141.2	185.4	214.4	232.8	250.8	212.3	147.3	120.1	20- 30	148.7	599.0	79.3,79.3
40	55.79	76.65	81.37	81.38	98.93	85.97	52.91	41.85	30- 40	73.73	672.7	89,89
50	29.43	36.86	36.79	34.72	43.38	40.42	27.21	25.15	40- 50	37.98	710.7	94.1,94.1
60	18.74	21.36	21.47	21.18	24.10	22.74	17.97	17.05	50- 60	23.79	734.5	97.2,97.2
70	8.168	9.376	10.46	11.08	11.68	10.38	8.541	7.814	60- 70	14.93	749.4	99.2,99.2
80	1.083	1.685	2.341	2.762	2.803	2.154	1.384	1.051	70- 80	5.615	755.0	99.9,99.9
90	0	0	0.0001	0.0117	0.0167	0	0	0	80- 90	0.5580	755.6	100,100
100	0	0	0	0	0	0	0	0	90-100	0.0001	755.6	100,100
110	0	0	0	0	0	0	0	0	100-110	0	755.6	100,100
120	0	0	0	0	0	0	0	0	110-120	0	755.6	100,100
130	0	0	0	0	0	0	0	0	120-130	0	755.6	100,100
140	0	0	0	0	0	0	0	0	130-140	0.0000	755.6	100,100
150	0.0296	0.0233	0.0154	0.0116	0.0071	0.0159	0.0157	0.0197	140-150	0.0032	755.6	100,100
160	0.1002	0.0876	0.0754	0.0686	0.0431	0.0473	0.0574	0.0660	150-160	0.0173	755.6	100,100
170	0.1584	0.1528	0.1459	0.1408	0.1032	0.1056	0.1138	0.1227	160-170	0.0276	755.6	100,100
180	0.0954	0.1037	0.0976	0.0974	0.1011	0.1039	0.1072	0.1098	170-180	0.0119	755.6	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.6DEG  
Operators:David  
Test Date:2014-12-22

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity:67.1%  
Test Distance:2.508m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:GC	SUR.:	PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2014-12-22

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.508m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: GC	SUR.:	PROTECTION ANGLE:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.169	.096	.030	.162	.093	.029	.150	.086	.027	.138	.080	.026	.128	.074	.024		
2.0	.160	.088	.027	.154	.085	.026	.144	.080	.025	.134	.075	.024	.125	.071	.022		
3.0	.150	.080	.024	.146	.078	.023	.137	.074	.023	.129	.070	.022	.121	.067	.021		
4.0	.141	.074	.022	.137	.072	.021	.130	.069	.021	.123	.066	.020	.116	.063	.019		
5.0	.133	.068	.020	.130	.067	.019	.123	.064	.019	.117	.062	.018	.111	.060	.018		
6.0	.126	.063	.018	.123	.062	.018	.117	.060	.017	.112	.058	.017	.107	.056	.017		
7.0	.119	.059	.017	.117	.058	.017	.112	.057	.016	.107	.055	.016	.103	.053	.016		
8.0	.114	.055	.016	.111	.055	.015	.107	.053	.015	.103	.052	.015	.099	.051	.015		
9.0	.108	.052	.015	.106	.052	.015	.102	.050	.014	.098	.049	.014	.095	.048	.014		
10.0	.103	.050	.014	.101	.049	.014	.098	.048	.013	.094	.047	.013	.091	.046	.013		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.191	.191	.191	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.171	.157	.146	.146	.135	.125	.100	.093	.087	.057	.054	.050	.018	.017	.016	
2.0	.155	.133	.114	.133	.114	.099	.091	.079	.069	.052	.046	.040	.017	.015	.013	
3.0	.142	.114	.091	.121	.098	.079	.083	.068	.056	.048	.040	.033	.015	.013	.011	
4.0	.130	.099	.074	.112	.085	.065	.077	.059	.046	.045	.035	.027	.014	.011	.009	
5.0	.121	.087	.062	.104	.075	.054	.071	.052	.038	.041	.031	.022	.013	.010	.007	
6.0	.113	.077	.052	.097	.067	.045	.067	.047	.032	.039	.028	.019	.013	.009	.006	
7.0	.106	.069	.044	.091	.060	.038	.063	.042	.027	.036	.025	.016	.012	.008	.005	
8.0	.099	.063	.038	.085	.055	.033	.059	.038	.023	.034	.023	.014	.011	.007	.005	
9.0	.094	.058	.033	.081	.050	.029	.056	.035	.020	.033	.021	.012	.011	.007	.004	
10.0	.089	.053	.029	.077	.046	.025	.053	.032	.018	.031	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2014-12-22

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.508m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm											
NAME:					TYPE:8TRSG4DIM/827NF30/B/H			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: GC					SUR.:			PROTECTION ANGLE:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		19.0	19.8	19.2	20.0	20.1	20.1	20.9	20.3	21.1	21.2
	3H	19.5	20.3	19.8	20.5	20.7	20.6	21.4	20.9	21.6	21.8
	4H	19.6	20.4	19.9	20.6	20.8	20.8	21.5	21.0	21.7	22.0
	6H	19.6	20.3	19.9	20.6	20.8	20.8	21.5	21.1	21.7	22.0
	8H	19.6	20.2	19.9	20.5	20.8	20.8	21.4	21.1	21.7	21.9
	12H	19.5	20.2	19.8	20.4	20.7	20.7	21.4	21.0	21.6	21.9
4H	2H	19.3	20.1	19.6	20.3	20.5	20.3	21.0	20.6	21.2	21.5
	3H	20.0	20.7	20.3	20.9	21.2	21.0	21.6	21.3	21.9	22.1
	4H	20.1	20.7	20.5	21.0	21.3	21.1	21.7	21.5	22.0	22.3
	6H	20.1	20.7	20.5	21.0	21.3	21.2	21.7	21.6	22.0	22.4
	8H	20.1	20.6	20.5	20.9	21.3	21.1	21.6	21.5	22.0	22.4
	12H	20.0	20.5	20.4	20.8	21.2	21.1	21.5	21.5	21.9	22.3
8H	4H	20.1	20.6	20.5	21.0	21.4	21.1	21.6	21.5	21.9	22.3
	6H	20.1	20.5	20.6	20.9	21.4	21.2	21.6	21.6	22.0	22.4
	8H	20.1	20.5	20.5	20.9	21.3	21.1	21.5	21.6	21.9	22.3
	12H	20.0	20.4	20.5	20.8	21.3	21.1	21.4	21.5	21.8	22.3
12H	4H	20.1	20.6	20.5	20.9	21.3	21.0	21.5	21.5	21.9	22.3
	6H	20.1	20.5	20.5	20.9	21.3	21.1	21.5	21.6	21.9	22.3
	8H	20.1	20.4	20.5	20.8	21.3	21.1	21.4	21.5	21.8	22.3
Variations with the observer position at spacings:											
S = 1.0H		+ 0.8 / - 1.1					+ 0.9 / - 1.2				
1.5H		+ 1.0 / - 1.0					+ 1.5 / - 1.0				
2.0H		+ 0.9 / - 0.9					+ 1.4 / - 0.9				

CIE Pub.117 Corrected 755.6 lm Total Lamp Luminous Flux.(8log(F/F0) = -1.0)

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2014-12-22

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.508m [K=1.0000]  
 Remarks:



## UTILIZATION FACTORS TABLE

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: GC	SUR.:	PROTECTION ANGLE:

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	85	78	74	84	78	74	83	77	74	70
0.80	92	86	82	92	86	82	90	85	81	77
1.00	97	91	87	96	91	87	95	91	86	82
1.25	101	96	92	100	95	92	98	94	91	86
1.50	104	99	96	103	98	95	101	97	94	89
2.00	107	103	99	106	102	99	103	100	97	92
2.50	109	105	102	108	104	101	104	102	99	93
3.00	111	107	104	109	106	103	106	103	101	95
4.00	113	110	108	111	109	106	107	105	104	97
5.00	115	112	110	112	110	109	108	107	105	98
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.6DEG  
 Operators:David  
 Test Date:2014-12-22

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity:67.1%  
 Test Distance:2.508m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: GC	SUR.:	PROTECTION ANGLE:

Conical surface Flux(90deg):

694.4 lm

%lum = 91.9%


%lamp = 91.9%

Conical surface Flux(20deg):

734.47 lm

%lum = 97.2%

%lamp = 97.2%




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.6DEG  
Operators:David  
Test Date:2014-12-22

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity:67.1%  
Test Distance:2.508m [K=1.0000]  
Remarks:

## AAI Figure

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: GC	SUR.:	PROTECTION ANGLE:

Flux out:272.8 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.6DEG  
 Operators: David  
 Test Date: 2014-12-22

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity: 67.1%  
 Test Distance: 2.508m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm		
NAME:	TYPE:8TRSG4DIM/827NF30/B/H	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: GC	SUR.:	PROTECTION ANGLE:



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.6DEG  
Operators: David  
Test Date: 2014-12-22

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity: 67.1%  
Test Distance: 2.508m [K=1.0000]  
Remarks:

## Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.6DEG  
Operators: David  
Test Date: 2014-12-22

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
Humidity: 67.1%  
Test Distance: 2.508m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.0V I:0.0752A P:8.296W PF:0.9175 Lamp Flux:755.625x1 lm																		
NAME:									TYPE:8TRSG4DIM/827NF30/B/H									WEIGHT:
SPEC.:									DIM.:									SERIAL No.:
MFR.: GC									SUR.:									PROTECTION ANGLE:

Table--1


UNIT: cd

C (DEG) γ (DEG)	0	23	45	68	90	113	135	158	180	203	225	248	270	293	315	338			
0	2357	2357	2358	2359	2361	2362	2363	2363	2357	2357	2358	2359	2361	2362	2363	2363			
5	1982	2032	2093	2158	2219	2261	2284	2275	2253	2204	2148	2088	2033	1993	1978	1981			
10	1337	1403	1496	1602	1689	1750	1777	1759	1740	1659	1564	1478	1409	1367	1344	1351			
15	776	825	906	1006	1090	1149	1174	1160	1151	1080	1001	919	846	797	778	778			
20	417	455	510	586	647	691	706	692	685	630	572	516	462	418	402	407			
25	235	264	299	334	369	394	405	406	404	373	337	296	252	225	212	219			
30	141	162	185	206	214	225	233	243	251	236	212	177	147	128	120	129			
35	85.9	103	117	129	129	133	137	146	159	152	135	109	87.7	69.9	68.7	76.6			
40	55.8	67.5	76.6	81.3	81.4	78.9	81.4	90.0	98.9	97.6	86.0	68.8	52.9	41.6	41.9	48.6			
45	39.1	45.6	51.8	54.8	53.3	48.3	50.3	57.5	63.8	64.7	57.2	46.4	35.5	30.3	30.4	34.2			
50	29.4	32.8	36.9	38.6	36.8	33.5	34.7	38.9	43.4	43.7	40.4	33.4	27.2	25.0	25.2	27.0			
55	23.6	25.4	27.8	29.1	27.6	26.0	26.6	29.0	31.6	31.1	29.8	25.6	22.3	21.0	21.1	22.3			
60	18.7	19.9	21.4	22.4	21.5	20.9	21.2	22.6	24.1	23.4	22.7	20.1	18.0	17.1	17.1	17.9			
65	13.6	14.2	15.1	16.0	15.7	15.8	16.1	16.8	17.7	16.8	16.3	14.7	13.3	12.7	12.6	13.1			
70	8.17	8.73	9.38	10.2	10.5	10.8	11.1	11.5	11.7	11.0	10.4	9.42	8.54	7.95	7.81	8.03			
75	4.10	4.48	4.90	5.33	5.71	5.97	6.19	6.28	6.29	5.97	5.55	5.01	4.48	4.12	3.99	4.06			
80	1.08	1.36	1.69	2.04	2.34	2.59	2.76	2.79	2.80	2.51	2.15	1.73	1.38	1.14	1.05	1.09			
85	0.17	0.21	0.26	0.31	0.38	0.42	0.45	0.45	0.47	0.41	0.35	0.28	0.23	0.18	0.17	0.17			
90	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
145	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01			
150	0.03	0.03	0.02	0.02	0.02	0.01	0.01	0.01	0.01	0.01	0.02	0.01	0.02	0.02	0.02	0.02			
155	0.06	0.05	0.05	0.04	0.04	0.03	0.03	0.03	0.02	0.02	0.02	0.03	0.03	0.04	0.04	0.04			
160	0.10	0.09	0.09	0.08	0.08	0.07	0.07	0.07	0.04	0.04	0.05	0.05	0.06	0.06	0.07	0.07			
165	0.13	0.13	0.12	0.12	0.11	0.11	0.10	0.10	0.07	0.07	0.08	0.08	0.09	0.09	0.10	0.10			
170	0.16	0.16	0.15	0.15	0.15	0.14	0.14	0.14	0.10	0.10	0.11	0.11	0.11	0.12	0.12	0.12			
175	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.13	0.10	0.10	0.11	0.10	0.11	0.11	0.11	0.11			
180	0.10	0.10	0.10	0.09	0.10	0.10	0.10	0.09	0.10	0.10	0.10	0.11	0.11	0.11	0.11	0.11			

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.6DEG  
 Operators: David  
 Test Date: 2014-12-22

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-R5000\_V2 SYSTEM V2.0.287  
 Humidity: 67.1%  
 Test Distance: 2.508m [K=1.0000]  
 Remarks:


I (cd)





1000 lm

$\kappa = 1$



F = 5000 lm  
 K = 0.7  
 Hcc = 0.0 m  
 Hfc = 0.0 m  
 Eave = 100 lx

	Pcc	Pw	Pfc
—————	70	50	30
—————	50	30	20

