

IES LM-79-08



MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai, China

Test Model: 6MR16DIM/827FL35

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
Reviewed by:	Hill Liu 
Report Number:	RKS161009002-10
Test Date:	2016-10-13 to 2016-10-14
Report Date:	2016-10-14
Approved by:	Bill Xiong 
Prepared By:	Bay Area Compliance Laboratories Corp. (Dongguan). Pu Long Cun 69, Puxinghu Industrial Area, Tangxia Town, Dongguan, Guangdong, P.R.China. Tel: +86-0769-86858888 Fax: +86-0769-86858588
Test Facility:	Test facility was located at Pu Long Cun 69, Puxinghu Industrial Area, Tangxia Town, Dongguan, Guangdong, P.R.China.
Accreditation:	The IAS Accreditation Number TL-460.

1. Product Description

General Information:

One sample was received on 2016-10-09 and used for testing.

Model Tested: 6MR16DIM/827FL35
Manufacturer: GREEN CREATIVE LTD
Brand Name: GREEN CREATIVE
Product Designation: Integral LED Lamp
Burning Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 120 VAC 60Hz
Rated Power: 6W
Nominal CCT: 2700K
Nominal Lumen Output: 480 lm
Nominal CRI: 82

2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-2002: Harmonic Emission Limits – Related Power Quality Requirements for Lighting
- IES TM-30-15: IES Method for Evaluating Light Source Color Rendition (This method is not in IAS accreditation scope)

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Test Range	Calibration date	Calibration due date
2.0m integrating sphere	EVERFINE	R98	11010018	R98	2015-11-09	2016-11-08
High accuracy array spectroradiometer	EVERFINE	HAAS-2000	1012016T	380-780nm	2016-03-10	2017-03-09
Digital Power Meter	EVERFINE	PF2010A	1011004	600V/20A	2016-07-11	2017-07-10
Digital CC&CV DC Power Supply	EVERFINE	WY305-V1	1101047	30V/5A	2016-07-07	2017-07-06
Temperature/humidity/clock	Victor	VC230	EE023	0~40°C0~90%	2016-03-21	2017-03-20
Standard Light Source	SENSING	N/A	LSD090808	N/A	2016-09-25	2017-09-24
Special zero-voltage synchronous switching AC	EVERFINE	DPS1010-YF	1011001T	30V/5A	2016-03-04	2017-03-03
AC Power Supply	EVERFINE	VPS1030 PWM	1012017	0-150V, 0-300V	2016-03-04	2017-03-03
DC Power Supply	EVERFINE	WY12010	1009009	30V/5A	2016-03-04	2017-03-03
Power Meter	YOKOGAWA	WT-210	91KB35700	15/30/60/150/300/600V	2016-03-04	2017-03-03
Goniophotometer	EVERFINE	GO-R5000	YG108492N10120001	1600mm,3000W/10A	2016-03-10	2017-03-09
Wireless Remote Sensor	N/A	433MHz	N/A	0°C~50°C;-20°C~60°C	2016-03-21	2017-03-20
Standard Light Source	EVERFINE	D908	1012003	N/A	2016-09-08	2017-09-07

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ during measurement. And relative humidity is less than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is $U=1.8\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=20\text{K}$ ($K=2$), at the 95% confidence level. The uncertainty of the CRI is $U=1.8(K=2)$, at the 95% confidence level.

The uncertainty of power meter AC current $U=0.19\%$ of rdg, AC Voltage $U=0.15\%$ of rdg, Power $U=0.20\%$ ($K=2$), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous intensity is $U=1.6\%$ ($K=2$), at the 95% confidence level.

Additional Test

The Additional Test item may not be covered by IESNA LM-79-2008. Additional test including power factor, off-state power and THD, was measured by Digital Power Meter after stabilized at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$. Test voltage for THD and power factor test would be equal to rated voltage or, in case of a voltage range, maximum value of that range.

The uncertainty of power meter AC current $U=0.19\%$ of rdg, AC Voltage $U=0.15\%$ of rdg, Power $U=0.20\%$ ($K=2$), at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-15 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Total operating time for integrating sphere test: **0.5hour**


Test orientation: **Downward**

Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
12.0	60	0.5232	5.82	0.9269	543.7	93.42

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
1.709	2658	0.00013	0.4636	0.4118	0.2644	0.5284


Color Rendering Index




Fidelity Index and Gamut Index

Fidelity Index R_f	83
Gamut Index R_g	95


Spectral Power Distribution Comparison




Plot of R_g versus R_f




Chroma Shift by Hue



R_f by Hue




Color Vector Graphic




— Reference Illuminat — Test Source

Color Fidelity by CES Sample




Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	2.740E-02	421	1.527E-01	462	3.507E+00	503	3.197E+00	544	5.842E+00
381	2.180E-02	422	1.620E-01	463	3.356E+00	504	3.290E+00	545	5.940E+00
382	2.080E-02	423	1.893E-01	464	3.300E+00	505	3.379E+00	546	6.034E+00
383	2.010E-02	424	2.184E-01	465	3.169E+00	506	3.473E+00	547	6.068E+00
384	1.800E-02	425	2.374E-01	466	3.122E+00	507	3.511E+00	548	6.164E+00
385	1.120E-02	426	2.828E-01	467	3.012E+00	508	3.604E+00	549	6.267E+00
386	1.320E-02	427	3.238E-01	468	2.971E+00	509	3.638E+00	550	6.301E+00
387	1.650E-02	428	3.800E-01	469	2.859E+00	510	3.727E+00	551	6.400E+00
388	1.820E-02	429	4.214E-01	470	2.810E+00	511	3.815E+00	552	6.507E+00
389	2.040E-02	430	4.727E-01	471	2.689E+00	512	3.906E+00	553	6.614E+00
390	1.770E-02	431	5.433E-01	472	2.625E+00	513	3.940E+00	554	6.663E+00
391	8.700E-03	432	6.027E-01	473	2.506E+00	514	4.018E+00	555	6.780E+00
392	5.600E-03	433	6.862E-01	474	2.449E+00	515	4.042E+00	556	6.911E+00
393	1.160E-02	434	7.519E-01	475	2.339E+00	516	4.129E+00	557	6.960E+00
394	1.440E-02	435	8.558E-01	476	2.294E+00	517	4.220E+00	558	7.140E+00
395	1.650E-02	436	9.345E-01	477	2.252E+00	518	4.305E+00	559	7.198E+00
396	9.200E-03	437	1.012E+00	478	2.166E+00	519	4.329E+00	560	7.334E+00
397	5.500E-03	438	1.141E+00	479	2.149E+00	520	4.406E+00	561	7.457E+00
398	3.100E-03	439	1.238E+00	480	2.102E+00	521	4.424E+00	562	7.509E+00
399	1.700E-03	440	1.388E+00	481	2.110E+00	522	4.504E+00	563	7.653E+00
400	1.180E-02	441	1.507E+00	482	2.131E+00	523	4.583E+00	564	7.809E+00
401	1.430E-02	442	1.695E+00	483	2.119E+00	524	4.650E+00	565	7.950E+00
402	1.200E-02	443	1.845E+00	484	2.154E+00	525	4.669E+00	566	8.080E+00
403	1.200E-02	444	2.079E+00	485	2.151E+00	526	4.745E+00	567	8.212E+00
404	1.340E-02	445	2.276E+00	486	2.190E+00	527	4.817E+00	568	8.296E+00
405	2.550E-02	446	2.562E+00	487	2.199E+00	528	4.886E+00	569	8.448E+00
406	2.520E-02	447	2.780E+00	488	2.256E+00	529	4.899E+00	570	8.527E+00
407	2.720E-02	448	3.094E+00	489	2.319E+00	530	4.984E+00	571	8.688E+00
408	2.790E-02	449	3.319E+00	490	2.340E+00	531	5.071E+00	572	8.841E+00
409	4.090E-02	450	3.626E+00	491	2.399E+00	532	5.077E+00	573	8.995E+00
410	4.590E-02	451	3.812E+00	492	2.464E+00	533	5.147E+00	574	9.146E+00
411	3.950E-02	452	4.068E+00	493	2.492E+00	534	5.225E+00	575	9.298E+00
412	3.250E-02	453	4.158E+00	494	2.568E+00	535	5.236E+00	576	9.365E+00
413	4.190E-02	454	4.292E+00	495	2.611E+00	536	5.307E+00	577	9.520E+00
414	4.980E-02	455	4.255E+00	496	2.696E+00	537	5.389E+00	578	9.677E+00
415	5.540E-02	456	4.267E+00	497	2.787E+00	538	5.419E+00	579	9.829E+00
416	7.400E-02	457	4.134E+00	498	2.829E+00	539	5.562E+00	580	9.976E+00
417	7.720E-02	458	4.073E+00	499	2.919E+00	540	5.582E+00	581	1.004E+01
418	9.570E-02	459	3.878E+00	500	3.010E+00	541	5.659E+00	582	1.017E+01
419	1.083E-01	460	3.786E+00	501	3.058E+00	542	5.673E+00	583	1.031E+01
420	1.235E-01	461	3.601E+00	502	3.154E+00	543	5.757E+00	584	1.037E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	1.051E+01	626	1.100E+01	667	5.528E+00	708	1.816E+00	749	3.909E-01
586	1.064E+01	627	1.091E+01	668	5.397E+00	709	1.742E+00	750	4.102E-01
587	1.078E+01	628	1.083E+01	669	5.284E+00	710	1.670E+00	751	4.146E-01
588	1.092E+01	629	1.076E+01	670	5.148E+00	711	1.612E+00	752	3.992E-01
589	1.096E+01	630	1.065E+01	671	5.041E+00	712	1.586E+00	753	3.719E-01
590	1.106E+01	631	1.047E+01	672	4.920E+00	713	1.524E+00	754	3.234E-01
591	1.119E+01	632	1.037E+01	673	4.792E+00	714	1.479E+00	755	3.012E-01
592	1.130E+01	633	1.026E+01	674	4.660E+00	715	1.428E+00	756	2.845E-01
593	1.131E+01	634	1.015E+01	675	4.557E+00	716	1.368E+00	757	2.197E-01
594	1.141E+01	635	9.973E+00	676	4.442E+00	717	1.331E+00	758	2.059E-01
595	1.151E+01	636	9.864E+00	677	4.306E+00	718	1.293E+00	759	2.016E-01
596	1.160E+01	637	9.753E+00	678	4.201E+00	719	1.242E+00	760	1.939E-01
597	1.159E+01	638	9.622E+00	679	4.105E+00	720	1.197E+00	761	2.167E-01
598	1.167E+01	639	9.438E+00	680	3.994E+00	721	1.166E+00	762	2.588E-01
599	1.175E+01	640	9.324E+00	681	3.929E+00	722	1.150E+00	763	2.431E-01
600	1.182E+01	641	9.144E+00	682	3.822E+00	723	1.098E+00	764	1.954E-01
601	1.190E+01	642	9.014E+00	683	3.720E+00	724	1.061E+00	765	1.712E-01
602	1.188E+01	643	8.941E+00	684	3.617E+00	725	1.021E+00	766	1.691E-01
603	1.193E+01	644	8.757E+00	685	3.502E+00	726	9.674E-01	767	1.936E-01
604	1.197E+01	645	8.616E+00	686	3.413E+00	727	9.496E-01	768	1.849E-01
605	1.201E+01	646	8.482E+00	687	3.336E+00	728	9.349E-01	769	1.642E-01
606	1.196E+01	647	8.348E+00	688	3.241E+00	729	9.194E-01	770	1.351E-01
607	1.198E+01	648	8.151E+00	689	3.139E+00	730	8.837E-01	771	1.386E-01
608	1.200E+01	649	8.024E+00	690	3.051E+00	731	8.634E-01	772	1.459E-01
609	1.201E+01	650	7.896E+00	691	2.965E+00	732	8.206E-01	773	1.309E-01
610	1.201E+01	651	7.768E+00	692	2.902E+00	733	7.755E-01	774	1.345E-01
611	1.192E+01	652	7.594E+00	693	2.814E+00	734	7.544E-01	775	1.284E-01
612	1.191E+01	653	7.454E+00	694	2.739E+00	735	7.237E-01	776	1.201E-01
613	1.191E+01	654	7.337E+00	695	2.647E+00	736	6.887E-01	777	1.111E-01
614	1.190E+01	655	7.153E+00	696	2.571E+00	737	6.389E-01	778	1.088E-01
615	1.186E+01	656	7.041E+00	697	2.507E+00	738	6.046E-01	779	1.092E-01
616	1.175E+01	657	6.869E+00	698	2.420E+00	739	5.966E-01	780	9.680E-02
617	1.172E+01	658	6.739E+00	699	2.337E+00	740	5.998E-01		
618	1.168E+01	659	6.581E+00	700	2.288E+00	741	5.860E-01		
619	1.163E+01	660	6.448E+00	701	2.235E+00	742	5.637E-01		
620	1.158E+01	661	6.322E+00	702	2.149E+00	743	5.072E-01		
621	1.145E+01	662	6.203E+00	703	2.081E+00	744	4.685E-01		
622	1.138E+01	663	6.036E+00	704	2.013E+00	745	4.290E-01		
623	1.131E+01	664	5.915E+00	705	1.949E+00	746	4.031E-01		
624	1.123E+01	665	5.795E+00	706	1.916E+00	747	4.162E-01		
625	1.108E+01	666	5.651E+00	707	1.868E+00	748	4.069E-01		

CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0 hours**

Test orientation: **Downward**


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
12.0	60	0.5330	5.93	0.9280

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I_{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
547.9	92.39	1400.7	0.56	0.56

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I_{max}):	33.5	33.8	33.8	33.4	33.6
Field Angle (10% I_{max}):	56.9	57.4	57.3	56.3	57.0

Luminous Intensity (cd) Distribution Data

C y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	1401	1401	1401	1401	1401	1401	1401	1401
5.0°	1358	1347	1337	1334	1331	1334	1337	1347
10.0°	1153	1125	1104	1093	1099	1110	1132	1162
15.0°	803	769	747	733	740	757	788	830
20.0°	469	443	431	416	408	413	426	458
25.0°	244	238	229	221	209	198	197	204
30.0°	120	118	116	115	106	90	85	87
35.0°	57	53	55	58	51	43	41	42
40.0°	29	26	28	31	28	24	24	24
45.0°	17	17	18	18	17	15	15	15
50.0°	13	13	13	13	12	11	11	11
55.0°	11	10	11	11	10	9	9	9
60.0°	10	9	9	10	9	9	9	8
65.0°	9	9	8	9	8	8	8	8
70.0°	7	7	7	7	7	7	7	7
75.0°	6	6	6	6	6	6	6	6
80.0°	5	5	5	4	4	5	5	5
85.0°	3	3	3	3	3	3	4	4
90.0°	2	2	2	2	2	2	2	2
95.0°	1	1	1	1	2	2	2	2
100.0°	1	1	1	1	1	1	1	1
105.0°	1	1	1	1	1	1	1	1
110.0°	1	1	1	1	1	1	1	1
115.0°	1	1	1	1	1	1	1	1
120.0°	1	1	1	1	1	1	1	1
125.0°	1	1	1	1	1	1	1	1
130.0°	1	1	1	1	1	1	1	1
135.0°	1	1	1	1	1	1	1	1
140.0°	1	1	1	1	1	1	1	1
145.0°	1	1	1	1	1	1	1	1
150.0°	1	1	1	1	1	1	1	1
155.0°	1	1	1	1	1	1	1	1
160.0°	1	1	1	1	1	1	1	1
165.0°	1	1	1	1	1	1	1	1
170.0°	1	1	1	1	1	1	1	1
175.0°	1	1	1	1	1	1	1	1
180.0°	0	0	0	0	0	0	0	0

Luminous Intensity (cd) Distribution Data (cont.)

C y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	1401	1401	1401	1401	1401	1401	1401	1401
5.0°	1345	1356	1365	1368	1374	1377	1372	1365
10.0°	1163	1191	1214	1234	1239	1222	1200	1170
15.0°	849	899	931	947	938	904	862	821
20.0°	477	529	556	573	563	527	491	466
25.0°	207	223	242	258	261	249	239	232
30.0°	85	88	95	107	109	107	107	111
35.0°	41	42	45	51	51	49	48	52
40.0°	24	25	26	29	28	26	26	27
45.0°	15	16	17	18	18	16	16	16
50.0°	11	11	12	13	13	12	12	12
55.0°	9	10	10	11	10	10	10	10
60.0°	9	9	9	9	9	9	9	9
65.0°	8	8	8	9	9	8	9	9
70.0°	7	7	8	8	8	8	7	7
75.0°	6	6	6	7	7	7	7	6
80.0°	5	5	5	6	6	5	5	5
85.0°	4	4	4	4	4	4	4	4
90.0°	2	3	3	3	3	2	2	2
95.0°	2	2	2	2	2	2	2	2
100.0°	1	1	1	1	1	1	1	1
105.0°	1	1	1	1	1	1	1	1
110.0°	1	1	1	1	1	1	1	1
115.0°	1	1	1	1	1	1	1	1
120.0°	1	1	1	1	1	1	1	1
125.0°	1	1	1	1	1	1	1	1
130.0°	1	1	1	1	1	1	1	1
135.0°	1	1	1	1	1	1	1	1
140.0°	1	1	1	1	1	1	1	1
145.0°	1	1	1	1	1	1	1	1
150.0°	1	1	1	1	1	1	1	1
155.0°	1	1	1	1	1	1	1	1
160.0°	1	1	1	1	1	1	1	1
165.0°	1	1	1	1	1	1	1	1
170.0°	1	1	1	1	1	1	1	1
175.0°	1	1	1	1	1	1	1	1
180.0°	0	0	0	0	0	0	0	0


Zonal Lumen Density Measurement

Deg	Flux (lm)	%	Deg	Flux (lm)	%
0-5	32.9	6.01	0-5	32.9	6.01
5-10	90.0	16.43	0-10	122.9	22.44
10-15	118.4	21.60	0-15	241.3	44.04
15-20	108.0	19.70	0-20	349.3	63.74
20-25	74.0	13.51	0-25	423.3	77.26
25-30	41.9	7.65	0-30	465.2	84.90
30-35	22.3	4.08	0-35	487.5	88.98
35-40	12.6	2.29	0-40	500.1	91.27
40-45	7.9	1.45	0-45	508.0	92.71
45-50	5.7	1.05	0-50	513.7	93.76
50-55	4.8	0.88	0-55	518.5	94.64
55-60	4.4	0.80	0-60	522.9	95.44
60-65	4.2	0.77	0-65	527.2	96.21
65-70	3.9	0.72	0-70	531.1	96.93
70-75	3.5	0.65	0-75	534.6	97.58
75-80	3.0	0.55	0-80	537.7	98.13
80-85	2.3	0.42	0-85	540.0	98.55
85-90	1.6	0.29	0-90	541.5	98.84
90-95	1.0	0.19	0-95	542.6	99.03
95-100	0.7	0.14	0-100	543.3	99.16
100-105	0.6	0.10	0-105	543.9	99.27
105-110	0.5	0.09	0-110	544.4	99.35
110-115	0.4	0.08	0-115	544.8	99.43
115-120	0.4	0.07	0-120	545.2	99.51
120-125	0.4	0.07	0-125	545.6	99.58
125-130	0.4	0.07	0-130	546.0	99.64
130-135	0.3	0.06	0-135	546.3	99.71
135-140	0.3	0.06	0-140	546.6	99.77
140-145	0.3	0.05	0-145	546.9	99.82
145-150	0.3	0.05	0-150	547.2	99.86
150-155	0.2	0.04	0-155	547.4	99.91
155-160	0.2	0.03	0-160	547.6	99.94
160-165	0.1	0.03	0-165	547.7	99.97
165-170	0.1	0.02	0-170	547.8	99.99
170-175	0.1	0.01	0-175	547.9	100.00
175-180	0.0	0.00	0-180	547.9	100.00

6. Product Photo



7. Product Test orientation in the Goniophotometer



*****END OF REPORT*****