

IES LM-79-08

MEASUREMENT AND TEST REPORT

For

GREEN CREATIVE LTD

756 North Zhongshan Rd., Unit B301 Zhabei District, Shanghai, China

Test Model: 8PAR20DIM/940NF25

Report Type:	Electrical and Photometric tests including: Luminous Flux, Chromaticity, Luminous Intensity Distribution
Test Engineer:	Hill Liu <i>Hill Liu</i>
Report Number:	R1KS170216011-10A1
Test Date:	2017-03-05 to 2017-03-07
Report Date:	2017-04-01
Reviewed By:	Bill Xiong / EE Engineer <i>Bill Xiong</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Dongguan). No.69,Pulongcun ,Puxinhu Industrial Area, Tangxia , Dongguan, Guangdong, China. Tel: +86-0769-86858888 Fax:+86-0769-86858588
Accreditation:	The IAS Accreditation Number TL-460.

1. Product Description

General Information:

Two samples were received on 2017-02-16. One was tested in integrating sphere and the other was tested in goniophotometer

Model Tested: 8PAR20DIM/940NF25
Manufacturer: GREEN CREATIVE LTD
Brand Name: GREEN CREATIVE
Product Designation: Directional LED Lamp
Burning Time Before Test: 0hour(For New Products)

Rated Values:

Rated Voltage/Frequency: 120 V AC 60Hz
Rated Power: 8 W
Nominal CCT: 4000K
Nominal Lumen Output: 570 lm

2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-2002: Harmonic Emission Limits – Related Power Quality Requirements for Lighting
- IES TM-30-15: IES Method for Evaluating Light Source Color Rendition (This method is not in IAS accreditation scope)

3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Test Range	Calibration date	Calibration due date
Integrating Sphere	SENSING	SPR-600	S09008	25~50°C	2017-03-09	2018-03-08
High Accuracy Array spectroradiometer	EVERFINE	HAAS-2000	M112048CA1361125	380-780nm	2016-07-08	2017-07-07
Power meter	YOKOGAWA	WT310	C20E17024V	2kV/20A	2016-07-08	2017-07-07
DC Power Supply	ITECH	IT6154	0061 0417 6471 0010 19	0~32V	2017-03-03	2018-03-02
Thermal Meter	SENSING	N/A	N/A	25、50°C	2017-03-09	2018-03-08
Standard Light Source	SENSING	N/A	LSD090808	N/A	2016-12-05	2017-12-04
AC Power Supply	ALL Power	APW-105N	970613	220V±10% 50Hz	2017-03-03	2018-03-02
AC Power Supply	EVERFINE	VPS1030 PWM	1012017	0-150V, 0-300V	2017-03-03	2018-03-02
DC Power Supply	EVERFINE	WY12010	1009009	30V/5A	2017-03-03	2018-03-02
Power Meter	YOKOGAWA	WT-210	91KB35700	15/30/60/150/300/600 V	2017-03-03	2018-03-02
Goniophotometer	EVERFINE	GO-R5000	YG108492N10120001	1600mm,3000W/10A	2017-03-09	2018-03-08
Wireless Remote Sensor	N/A	433MHz	N/A	0°C~50°C;-20°C~60°C	2017-03-20	2018-03-19

Device	Manufacture	Model No	Serial No	Test Range	Calibration date	Calibration due date
Standard Light Source	EVERFINE	D908	1012003	N/A	2016-09-07	2017-09-06

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ during measurement. And relative humidity is less than 65%.

Integrating Sphere System

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4 π geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is $U=1.8\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=20\text{K}$ ($K=2$), at the 95% confidence level. The uncertainty of the CRI is $U=1.8(K=2)$, at the 95% confidence level.

The uncertainty of power meter AC current $U=0.19\%$ of rdg, AC Voltage $U=0.15\%$ of rdg, Power $U=0.20\%$ ($K=2$), at the 95% confidence level.

Goniophotometer System

The goniophotometer system is calibrated by standard light source before measurement.

Type C goniophotometer was used for measuring total luminous flux, luminous intensity distribution, and color spatial uniformity. The product was operated in its intended orientation in application and was recorded in this report. The vertical angle (γ) test intervals were set no more than 1 degree while data for 5 degree intervals is reported. The horizontal angle (C plane) test intervals were set no more than 22.5 degree.

The uncertainty of the luminous intensity is $U=1.6\%$ ($K=2$) , at the 95% confidence level.

Fidelity Index and Gamut Index Calculation

The R_i , R_g was calculated according to IES TM-30-15 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

5. Test Result

[Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Base up**


Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.06998	7.915	0.9426	707.81	89.42

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
2.3938	3848	0.00288	0.3897	0.3886	0.2264	0.5081

Color Rendering Index


Ra			
92.0			
R1	R2	R3	R4
92	95	97	91
R5	R6	R7	R8
90	93	94	84
R9	R10	R11	R12
61	88	90	72
R13	R14	R15	
93	98	89	




Fidelity Index and Gamut Index

Fidelity Index R_f	89
Gamut Index R_g	97


Spectral Power Distribution Comparison




Plot of R_g versus R_f




Chroma Shift by Hue



R_f by Hue




Color Vector Graphic




— Reference Illuminat — Test Source

Color Fidelity by CES Sample




Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	1.476E-01	421	7.430E-01	462	8.365E+00	503	6.912E+00	544	9.671E+00
381	1.176E-01	422	8.207E-01	463	7.986E+00	504	7.025E+00	545	9.726E+00
382	1.052E-01	423	8.954E-01	464	7.624E+00	505	7.117E+00	546	9.772E+00
383	9.894E-02	424	9.847E-01	465	7.360E+00	506	7.219E+00	547	9.829E+00
384	9.713E-02	425	1.079E+00	466	7.102E+00	507	7.324E+00	548	9.864E+00
385	1.005E-01	426	1.187E+00	467	6.878E+00	508	7.429E+00	549	9.925E+00
386	8.393E-02	427	1.289E+00	468	6.678E+00	509	7.510E+00	550	9.935E+00
387	8.920E-02	428	1.429E+00	469	6.516E+00	510	7.603E+00	551	9.985E+00
388	7.188E-02	429	1.543E+00	470	6.348E+00	511	7.689E+00	552	1.001E+01
389	8.698E-02	430	1.681E+00	471	6.154E+00	512	7.755E+00	553	1.006E+01
390	6.526E-02	431	1.827E+00	472	5.979E+00	513	7.849E+00	554	1.009E+01
391	6.297E-02	432	1.982E+00	473	5.802E+00	514	7.901E+00	555	1.012E+01
392	4.981E-02	433	2.153E+00	474	5.631E+00	515	8.011E+00	556	1.017E+01
393	5.693E-02	434	2.312E+00	475	5.450E+00	516	8.057E+00	557	1.020E+01
394	5.792E-02	435	2.516E+00	476	5.306E+00	517	8.116E+00	558	1.021E+01
395	5.351E-02	436	2.723E+00	477	5.180E+00	518	8.180E+00	559	1.024E+01
396	6.127E-02	437	2.964E+00	478	5.064E+00	519	8.257E+00	560	1.026E+01
397	5.950E-02	438	3.197E+00	479	4.994E+00	520	8.322E+00	561	1.031E+01
398	5.965E-02	439	3.476E+00	480	4.926E+00	521	8.398E+00	562	1.033E+01
399	6.774E-02	440	3.773E+00	481	4.903E+00	522	8.442E+00	563	1.033E+01
400	6.988E-02	441	4.102E+00	482	4.892E+00	523	8.512E+00	564	1.038E+01
401	7.119E-02	442	4.466E+00	483	4.901E+00	524	8.567E+00	565	1.039E+01
402	7.953E-02	443	4.852E+00	484	4.949E+00	525	8.615E+00	566	1.041E+01
403	8.827E-02	444	5.290E+00	485	4.999E+00	526	8.679E+00	567	1.043E+01
404	9.096E-02	445	5.771E+00	486	5.071E+00	527	8.745E+00	568	1.047E+01
405	1.010E-01	446	6.267E+00	487	5.132E+00	528	8.796E+00	569	1.047E+01
406	1.215E-01	447	6.818E+00	488	5.222E+00	529	8.858E+00	570	1.051E+01
407	1.359E-01	448	7.379E+00	489	5.304E+00	530	8.909E+00	571	1.053E+01
408	1.504E-01	449	7.979E+00	490	5.408E+00	531	8.981E+00	572	1.055E+01
409	1.685E-01	450	8.559E+00	491	5.522E+00	532	9.035E+00	573	1.057E+01
410	2.010E-01	451	9.097E+00	492	5.602E+00	533	9.109E+00	574	1.059E+01
411	2.177E-01	452	9.598E+00	493	5.731E+00	534	9.152E+00	575	1.061E+01
412	2.524E-01	453	9.986E+00	494	5.848E+00	535	9.194E+00	576	1.063E+01
413	2.862E-01	454	1.025E+01	495	5.947E+00	536	9.259E+00	577	1.067E+01
414	3.211E-01	455	1.040E+01	496	6.069E+00	537	9.314E+00	578	1.068E+01
415	3.736E-01	456	1.037E+01	497	6.182E+00	538	9.362E+00	579	1.070E+01
416	4.207E-01	457	1.023E+01	498	6.315E+00	539	9.443E+00	580	1.074E+01
417	4.730E-01	458	9.972E+00	499	6.443E+00	540	9.455E+00	581	1.076E+01
418	5.338E-01	459	9.624E+00	500	6.565E+00	541	9.512E+00	582	1.077E+01
419	5.973E-01	460	9.212E+00	501	6.669E+00	542	9.578E+00	583	1.082E+01
420	6.640E-01	461	8.790E+00	502	6.779E+00	543	9.621E+00	584	1.081E+01

nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	1.084E+01	626	1.129E+01	667	7.431E+00	708	3.004E+00	749	9.674E-01
586	1.088E+01	627	1.126E+01	668	7.303E+00	709	2.935E+00	750	9.318E-01
587	1.090E+01	628	1.121E+01	669	7.164E+00	710	2.857E+00	751	9.093E-01
588	1.095E+01	629	1.115E+01	670	7.054E+00	711	2.778E+00	752	8.794E-01
589	1.098E+01	630	1.109E+01	671	6.932E+00	712	2.707E+00	753	8.600E-01
590	1.097E+01	631	1.104E+01	672	6.806E+00	713	2.637E+00	754	8.332E-01
591	1.103E+01	632	1.097E+01	673	6.665E+00	714	2.580E+00	755	8.136E-01
592	1.104E+01	633	1.094E+01	674	6.575E+00	715	2.520E+00	756	7.881E-01
593	1.106E+01	634	1.087E+01	675	6.427E+00	716	2.452E+00	757	7.626E-01
594	1.109E+01	635	1.079E+01	676	6.306E+00	717	2.382E+00	758	7.408E-01
595	1.114E+01	636	1.073E+01	677	6.205E+00	718	2.333E+00	759	7.200E-01
596	1.116E+01	637	1.065E+01	678	6.062E+00	719	2.261E+00	760	7.002E-01
597	1.120E+01	638	1.058E+01	679	5.953E+00	720	2.210E+00	761	6.789E-01
598	1.121E+01	639	1.050E+01	680	5.816E+00	721	2.144E+00	762	6.677E-01
599	1.125E+01	640	1.041E+01	681	5.720E+00	722	2.077E+00	763	6.415E-01
600	1.128E+01	641	1.032E+01	682	5.579E+00	723	2.040E+00	764	6.263E-01
601	1.133E+01	642	1.024E+01	683	5.487E+00	724	1.975E+00	765	6.061E-01
602	1.133E+01	643	1.015E+01	684	5.366E+00	725	1.922E+00	766	5.839E-01
603	1.135E+01	644	1.004E+01	685	5.265E+00	726	1.860E+00	767	5.735E-01
604	1.137E+01	645	9.957E+00	686	5.143E+00	727	1.819E+00	768	5.524E-01
605	1.139E+01	646	9.864E+00	687	5.022E+00	728	1.765E+00	769	5.365E-01
606	1.143E+01	647	9.775E+00	688	4.917E+00	729	1.723E+00	770	5.201E-01
607	1.143E+01	648	9.668E+00	689	4.805E+00	730	1.674E+00	771	5.056E-01
608	1.145E+01	649	9.571E+00	690	4.710E+00	731	1.623E+00	772	4.905E-01
609	1.146E+01	650	9.456E+00	691	4.603E+00	732	1.580E+00	773	4.746E-01
610	1.146E+01	651	9.338E+00	692	4.488E+00	733	1.533E+00	774	4.635E-01
611	1.149E+01	652	9.237E+00	693	4.397E+00	734	1.491E+00	775	4.456E-01
612	1.150E+01	653	9.105E+00	694	4.293E+00	735	1.448E+00	776	4.333E-01
613	1.151E+01	654	9.016E+00	695	4.184E+00	736	1.404E+00	777	4.243E-01
614	1.150E+01	655	8.884E+00	696	4.079E+00	737	1.359E+00	778	4.102E-01
615	1.152E+01	656	8.776E+00	697	3.974E+00	738	1.328E+00	779	4.114E-01
616	1.150E+01	657	8.631E+00	698	3.887E+00	739	1.281E+00	780	4.121E-01
617	1.151E+01	658	8.519E+00	699	3.794E+00	740	1.247E+00		
618	1.148E+01	659	8.421E+00	700	3.708E+00	741	1.210E+00		
619	1.145E+01	660	8.284E+00	701	3.603E+00	742	1.178E+00		
620	1.146E+01	661	8.169E+00	702	3.514E+00	743	1.142E+00		
621	1.144E+01	662	8.039E+00	703	3.418E+00	744	1.108E+00		
622	1.142E+01	663	7.928E+00	704	3.337E+00	745	1.075E+00		
623	1.138E+01	664	7.801E+00	705	3.258E+00	746	1.050E+00		
624	1.136E+01	665	7.672E+00	706	3.166E+00	747	1.012E+00		
625	1.132E+01	666	7.551E+00	707	3.092E+00	748	9.897E-01		

CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



[Goniophotometer System]

Total operating time for luminous intensity distribution: **1.0 hours**

Test orientation: **Base up**


Electrical Measurement

Input Voltage (V)	Frequency (Hz)	Input Current (A)	Power (W)	Power Factor
120.0	60	0.0707	7.998	0.9427

Photometric Measurement

Luminous Flux (lm)	Efficacy (lm/W)	I_{max} (cd)	S/MH (C0/180)	S/MH (C90/270)
712.203	89.05	4121	0.38	0.37

Luminous Intensity Distribution



	C0/180	C45/225	C90/270	C135/315	AVG.
Beam Angle (50% I_{max}):	19.8	20.2	20.4	19.8	20.1
Field Angle (10% I_{max}):	37.8	38.7	38.6	37.7	38.2

Luminous Intensity (cd) Distribution Data

C y	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°
0.0°	3998	3998	3998	3998	3998	3998	3998	3998
5.0°	3032	3025	3071	3146	3258	3371	3497	3619
10.0°	1597	1625	1711	1783	1895	1971	2116	2272
15.0°	685	720	773	839	856	869	920	977
20.0°	258	276	298	322	319	329	336	371
25.0°	122	123	131	135	141	143	145	153
30.0°	63	67	71	71	71	72	77	81
35.0°	42	43	46	46	45	46	48	50
40.0°	32	33	34	34	33	34	35	37
45.0°	26	28	29	28	27	27	28	30
50.0°	23	24	25	24	23	23	24	25
55.0°	20	21	22	21	21	21	21	22
60.0°	16	16	16	16	16	17	18	19
65.0°	11	12	12	12	12	12	13	14
70.0°	8	8	8	8	8	9	10	10
75.0°	5	5	5	5	5	6	6	7
80.0°	2	2	2	3	3	3	4	4
85.0°	1	0	0	1	1	1	1	2
90.0°	0	0	0	0	0	0	0	0
95.0°	0	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	0	0	0	0	0	0	0	0
150.0°	0	0	0	0	0	0	0	0
155.0°	0	0	0	0	0	0	0	0
160.0°	0	0	0	0	0	0	0	0
165.0°	0	0	0	0	0	0	0	0
170.0°	0	0	0	0	0	0	0	0
175.0°	0	0	0	0	0	0	0	0
180.0°	0	0	0	0	0	0	0	0

Luminous Intensity (cd) Distribution Data (cont.)

C y	180°	202.5°	225°	247.5°	270°	292.5°	315°	337.5°
0.0°	3998	3998	3998	3998	3998	3998	3998	3998
5.0°	3808	3865	3857	3791	3659	3479	3318	3174
10.0°	2517	2579	2582	2456	2287	2052	1833	1718
15.0°	1145	1208	1190	1117	1008	869	785	735
20.0°	420	440	436	416	372	323	289	273
25.0°	174	173	181	176	154	142	135	129
30.0°	88	93	95	92	86	75	69	66
35.0°	54	55	57	57	54	50	45	43
40.0°	39	40	41	41	39	37	33	32
45.0°	30	30	31	31	31	29	27	26
50.0°	26	25	25	25	26	25	23	23
55.0°	22	22	22	22	22	22	21	21
60.0°	19	19	19	19	19	18	17	16
65.0°	15	15	14	14	14	13	12	12
70.0°	11	11	11	11	10	10	9	8
75.0°	8	8	8	7	7	6	6	5
80.0°	5	5	5	4	4	4	3	3
85.0°	2	2	2	2	2	1	1	1
90.0°	0	0	0	0	0	0	0	0
95.0°	0	0	0	0	0	0	0	0
100.0°	0	0	0	0	0	0	0	0
105.0°	0	0	0	0	0	0	0	0
110.0°	0	0	0	0	0	0	0	0
115.0°	0	0	0	0	0	0	0	0
120.0°	0	0	0	0	0	0	0	0
125.0°	0	0	0	0	0	0	0	0
130.0°	0	0	0	0	0	0	0	0
135.0°	0	0	0	0	0	0	0	0
140.0°	0	0	0	0	0	0	0	0
145.0°	0	0	0	0	0	0	0	0
150.0°	0	0	0	0	0	0	0	0
155.0°	0	0	0	0	0	0	0	0
160.0°	0	0	0	0	0	0	0	0
165.0°	0	0	0	0	0	0	0	0
170.0°	0	0	0	0	0	0	0	0
175.0°	0	0	0	0	0	0	0	0
180.0°	0	0	0	0	0	0	0	0

Zonal Lumen Density Measurement

Deg	Flux (lm)	%
0-5	88.9	12.48
5-10	193.2	27.12
10-15	166.9	23.44
15-20	94.9	13.33
20-25	46.8	6.58
25-30	27.1	3.80
30-35	17.9	2.51
35-40	13.9	1.95
40-45	11.8	1.66
45-50	10.7	1.50
50-55	10.0	1.40
55-60	9.0	1.27
60-65	7.3	1.02
65-70	5.6	0.79
70-75	4.1	0.57
75-80	2.6	0.36
80-85	1.2	0.17
85-90	0.3	0.05
90-95	0.0	0.00
95-100	0.0	0.00
100-105	0.0	0.00
105-110	0.0	0.00
110-115	0.0	0.00
115-120	0.0	0.00
120-125	0.0	0.00
125-130	0.0	0.00
130-135	0.0	0.00
135-140	0.0	0.00
140-145	0.0	0.00
145-150	0.0	0.00
150-155	0.0	0.00
155-160	0.0	0.00
160-165	0.0	0.00
165-170	0.0	0.00
170-175	0.0	0.00
175-180	0.0	0.00

Deg	Flux (lm)	%
0-5	88.9	12.48
0-10	282.1	39.60
0-15	449.0	63.04
0-20	543.9	76.37
0-25	590.7	82.95
0-30	617.8	86.75
0-35	635.7	89.26
0-40	649.6	91.21
0-45	661.4	92.87
0-50	672.1	94.37
0-55	682.1	95.77
0-60	691.1	97.04
0-65	698.4	98.06
0-70	704.0	98.85
0-75	708.1	99.42
0-80	710.6	99.78
0-85	711.9	99.95
0-90	712.2	100.00
0-95	712.2	100.00
0-100	712.2	100.00
0-105	712.2	100.00
0-110	712.2	100.00
0-115	712.2	100.00
0-120	712.2	100.00
0-125	712.2	100.00
0-130	712.2	100.00
0-135	712.2	100.00
0-140	712.2	100.00
0-145	712.2	100.00
0-150	712.2	100.00
0-155	712.2	100.00
0-160	712.2	100.00
0-165	712.2	100.00
0-170	712.2	100.00
0-175	712.2	100.00
0-180	712.2	100.00

6. Product Photo



*****END OF REPORT*****